



NOTICE OF AWARD

MAR 06 2024

NOVEAULAB ASIA CORP.

Unit SS 105 DSL Bldg., 380 Del Monte Avenue,
 Quezon City, Metro Manila

Madam/Sir:

This is to advise you that your bid dated December 12, 2023 for PR 23-10-479; Public Bidding Procurement of Supply and Delivery of Various Laboratory Supplies, Materials and Equipment for the College of Agriculture, with a following Contract Price is hereby accepted;

Object of Bidding	Total Amount in Figures	Amount in Words
<p>2.) One (1) unit of BIOSAFETY CABINET <i>Specifications:</i> . External Size: (WxDxH): 700*650*1230mm (without base stand) . Internal Size (WxDxH): 600*500*540mm . Tested Opening: Safety Height 200mm(8") . Max Opening: 370mm(15") . Inflow Velocity: 0.53/1.025m/s . Down Flow Velocity: 0.33/0.025m/s . HEPA Filter: Two, 99.995% efficiency at 0.3µm. Filter life indicator . Front Window: Motorized. Single Layer toughened glass 5mm. anti UV . Noise: 67 dB . UV Lamp: 15W*1 UV timer, UV life indicator, emission of 253.7 nm for most efficient decontamination . LED Lamp: 8W*2 . Illumination: 1000Lux . Consumption: 700W . Socket: Two, total load of two sockets: 500W . Display: LCD Display . Control System: Microprocessor . Airflow System: 70% air recirculation, 30% air exhaust</p>	<p>Php 219,735.00</p>	<p>Two Hundred Nineteen Thousand Seven Hundred Thirty-Five Pesos</p>



. *Visual and Audio Alarm: Filter replacement, window over height, abnormal air flow velocity; High filter pressure alarm*

. *Materials: work zone - 304 stainless steel, main body - cold-rolled steel with anti-bacteria powder coating*

. *Work Surface Height: 750mm with optional base stand*

. *Power Supply: AC220V/60HZ*

. *Standard Accessory: LED Lamp*2, UV Lamp*1, Remote Control, Waterproof sockets*2, base stand*

. *Optional Accessory: SS Water tap*1, SS Gas tap*1*

With On Site Training

Offer: BRAND: BIOBASE
Model: CLASS II A2
External Size (W*D*H)
700*650*1920mm
Internal Size (W*D*H)
600*500*540mm
Tested Opening Safety height
200mm
Inflow Velocity: 0.53±0.025m/s
Down Flow Velocity:
0.33±0.025m/s
ULPA Filter: Two, 99.9995% efficiency at 0.12µm, filter life indicator
Front Window: Motorized. Single Layer toughened glass 5mm. Anti UV.
Noise: ≤65 dB
UV Lamp: 15W*1 UV timer, UV life indicator, emission of 253.7 nanometers for most efficient decontamination
LED Lamp: 8W*2
Illumination: ≥1000Lux
Consumption: ≤500W
Socket: Two, total load of two sockets: 500W
Display: LCD display: exhaust filter and downflow filter pressure, filter and UV lamp working time, inflow and downflow velocity, filter life, humidity and temperature,





<p>4.) One (1) unit of CENTRIFUGE <i>Specifications:</i> . Max Capacity: 6*50ml . Max Speed: 4000rpm . Max RCF: 2250xg . Timing Range: 99min . Speed Precision: 2% . Noise: 65dB . Consumption: 150w . Power Supply: AC220V, 50/60Hz . External Size: (L*W*H) mm 450*370*280 . Package Size: (L*W*H) mm: 470*400*375 . Rotor: Angle Rotor with additional Rotor - 10ml</p> <p><i>Offer: BRAND: BIOBASE Model: BKC-TL4B Max. Capacity: 6*50ml Max. Speed: 4000rpm Max. RCF: 2250×g Timing Range: 1~99min Speed Precision: ±2% Noise: ≤65dB Consumption: 150W Power Supply: AC220V, 50Hz 5A External Size(L*W*H) mm: 450*370*280</i></p>	<p>Php 58,580.00</p>	<p>Fifty-Eight Thousand Five Hundred Eighty Pesos</p>
<p>6.) Three (3) unit of DIGITAL BINOCULAR MICROSCOPE WITH CAMERA <i>Specifications:</i> - Binocular Head 300 inclined 3600 rotating . EWF: 10x/20 mm eyepieces . Left eyepiece with ±5 dioptr adjustment . Interpupillary distance adjustable from 48mm to 76mm . Reversed quintuple (5) nosepiece on ball bearings . Objectives: 4x, 10x, S40x & S100x oil. . Integrated X-Y rack less mechanical stage . Coaxial coarse and fine focus adjustment with rack stop . Height adjustable Abbe condenser N.A. 1.25 with iris diaphragm and filter holder</p>	<p>Php 286,431.00</p>	<p>Two Hundred Eighty-Six Thousand Four Hundred Thirty-One Pesos</p>



<p>. Illumination: Dimmable (NeoLED) Stage & Focusing . Mechanical Stage: at least 152/197 x 131 mm with at least 79 x 36 mm X-Y rackless movement. . Coaxial coarse and fine focus adjustment: 180 graduations . Precision: 1.11µm with 0.2mm per rotation . Course Adjustment are equipped with friction control - Rechargeable CAMERA . 5.0MP, 1/2.5-inch CMOS USB-2.0 Camera . 24 bits color depth . 7 frames/sec (2592 x 1944 pixels) or . 27 frames/sec (1280 x960 Pixels) . Dynamic range: at least 76db . Image Focus Alpha software . Calibration slide: micrometer 1mm/100 With On Site Training</p> <p>Offer: Brand/Model: BM38UIB Optical System: Infinite Optical System Viewing head: Seidentopf Binocular Viewing Head Inclined at 30°, interpupillary 47-78m, 360° Rotation Nosepiece: Backward Quadruple Nosepiece Eyepiece: Wide Field Eyepiece WF10X/20 Infinite plan achromatic objective: 4x/0.10, 10x/0.25, 40x/0.65, spring loaded, 100x/1.25, spring loaded, oil Stage: Rackless Double Layer Mechanical Stage 150X139mm, Moving Range 75X52mm Focusing: Coaxial Coarse and Fine Adjustment, Fine Division 0.002mm, Coarse Stroke 37.7mm per Rotation, Fine Stroke 0.2mm per Rotation, Moving Range 25mm Condenser: NA1.25 Abbe Condenser with Aperture Diaphragm</p>		
---	--	--



<p>illumination: LED illumination for long life, brightness adjustable Supplied with: Dust cover, spare fuse, blue & green filters Power: 100-240V, 50/60Hz</p>		
<p>8.) One (1) unit of LABORATORY WATER DISTILLER <i>. Voltage: 110-120 volt</i> <i>. Water Flow Rate: 1 liter/minute or higher</i> <i>. Water Pressure: Minimum Pressure 3 p.s.i.</i> <i>. Distillate Temperature: 25-35 Degree C</i> <i>. Conductivity: 3.0 - 4.0 S per cm</i> <i>. Water Still Output: 4 liters/hour or higher</i> <i>. PH: 5.0 - 6.5</i> <i>. Resistivity: 0.25 - 0.30megohm</i></p> <p>Offer: BRAND: LASANY LPH-4 LPH4: 50cm ×15cm× 45cm Water Supply: Min. Flow Rate 1 Litre/min. Min. Pressure: 3 p.s.i. (0.2 ×105NM) Output: 4L/ hr Conductivity: 3.0-4.0µs/cm (using treated water) pH: 5.5-6.0</p>	<p>Php 62,450.00</p>	<p>Sixty-Two Thousand Four Hundred Fifty Pesos</p>
<p>11.) Three (3) unit of BENCH TOP pH METER</p> <p>Specifications: <i>. PH Range: 0.00~14.00ph</i> <i>. PH Accuracy: 0.05ph</i> <i>. Resolution: 0.01ph</i> <i>. Calibration Points: 2 points</i> <i>. Calibration solutions: (ph4.01/7.00/10.01)</i> <i>. mV Range: -1999~1999mV</i> <i>. mV Accuracy: 10mV</i> <i>. Resolution: 1mV</i> <i>. Temperature Compensation: 0~100 celcius, manual</i> <i>. Connector: BNC, 3.5mm jack socket</i> <i>. Display: LCD</i> <i>. Power Requirements: DC9V/400mA power adapter</i> <i>. Dimensions(mm): at least 210*205*65</i></p>	<p>Php 118,131.00</p>	<p>One Hundred Eighteen Thousand One Hundred Thirty-One Pesos</p>

M



<p><i>Offer: Model: PH950 Benchtop pH Meter</i> <i>Measuring Range: (0.00 ~ 14.00 pH</i> <i>Resolution: 0.1/0.01 pH</i> <i>Accuracy: ±0.01 pH ±1 digit</i> <i>Temperature Compensation Range: (0 to 100) °C (Auto. or Manual)</i> <i>Calibration point: 1 to 3 points</i> <i>Measuring Range: ±2000mV</i> <i>Resolution: 1mV</i> <i>Accuracy: ±0.1% FS ±1 digit</i> <i>Resolution: 0.01/0.1/1µS/cm 0.01/0.1 mS/cm</i> <i>Accuracy: ±1.0% FS ±1 digit</i> <i>Temperature Compensation Range (0 to 50) °C (Auto. or Manual)</i> <i>Cell constant: 0.1 / 1 / 10 cm-1</i> <i>Temp.: Measuring Range 0~100°C</i> <i>Thermistor: 30KΩ NTC</i></p>		
<p>13.) One (1) unit of ADJUSTABLE VOLUME PIPETTOR (10-100µl) <i>Specifications:</i> <ul style="list-style-type: none"> . Chemical resistant PTFE O-rings and seals that can handle solvents . PDF nozzle and PP shaft . Fully autoclavable . UV resistant for flexible sterilization . One touch calibration . Wetted materials are made up of at least stainless steel (SS) and polypropylene (PP) plunger assembly . Volume of 10-100µL . Increments of 0.1µL . Accuracy of ±2.0% to ±0.8% . Tip ejector is present . Comes with pipette tips (1000pcs/pack) <i>Offer: HiPette Fully Autoclave Mechanical Pipette</i></p>	<p>Php 10,474.00</p>	<p>Ten Thousand Four Hundred Seventy-Four Pesos</p>
<p>TOTAL CONTRACT PRICE</p>	<p>Php 755,801.00</p>	<p>Seven Hundred Fifty-Five Thousand Eight Hundred One Pesos Only</p>

You are hereby required to provide, within ten (10) days from receipt hereof, the Performance Security/ Performance Bond equivalent to the following;





Republic of the Philippines
WESTERN MINDANAO STATE UNIVERSITY
OFFICE OF THE PRESIDENT
 Normal Road, Baliwasan Zamboanga City
 Telefax.: 062-992-3084
www.wmsu.edu.ph



Form of Performance Security	Amount of Performance Security (Equal to Percentage of the Total Contract Price)
a) Cash or cashier's/manager's check issued by a Universal or Commercial Bank.	Five percent (5%)
b) Bank draft/ guarantee or irrevocable letter of credit issued by a Universal or Commercial Bank: Provided, however, that it shall be confirmed or authenticated by a Universal or Commercial Bank, if issued by a foreign bank	Five percent (5%)
c) Surety bond callable upon demand issued by a surety or insurance company duly certified by the insurance Commission as authorized to issue such security.	Thirty percent (30%)
d) Any combination of the foregoing.	Proportionate to share of form with respect to total amount of security

Failure to provide the Performance Security shall constitute sufficient ground for the cancellation of the award and forfeiture of the Bid Security.

Very truly yours,

MA. CARLA A. OCHOTORENA, RN., Ph.D.
 President

Received by:

 (Signature Over Printed Name)

Date: _____