



NOTICE OF AWARD

MAR 06 2024

PRINCE VALIANT INTERNATIONAL CORPORATION

Pvic Bldg., Lot 4E Lucky Home Subdivision
Brgy. Balabago, Jaro, Iloilo City

Madam/Sir:

This is to advise you that your bid dated January 16, 2024 for PR 23-09-415; Public Bidding Procurement of Purchase of Various Equipment for the College of Criminal Justice Education, with a following Contract Price is hereby accepted;

Object of Bidding	Total Amount in Figures	Amount in Words
<p>1.) Two (2) unit of Gun Executive Safe with Climate Monitoring <i>Specifications:</i> <i>Dimensions:</i> . 59.1 inches (H) x 22.8 inches (W) x 19.7 inches (D) <i>Exterior:</i> . Durable steel construction . Scratch-resistant powder coat finish . Predrilled mounting holes for easy installation Mounting kit with bolts included . Sturdy open/close spindle handle <i>Interior:</i> . Carpeted interior and floor to protect firearms . Adjustable/removable 14 gun rack . Temperature and humidity gauges to monitor storage conditions . UL listed programmable digital lock for secure access . Emergency access keys for backup entry <i>Fire Protection:</i> . 30-minute fire rating up to 760°C/1,400°F . Protects firearms and valuables from damage in the event of a fire</p> <p>Offer: Model: 3014D Brand: Honeywell (USA) 30 Min. Fire Rating Up to 760 C/1400 F</p>	<p>Php 300,000.00</p>	<p>Three Hundred Thousand Pesos</p>



<p>UL Listed Programmable Digital Lock Emergency Access Keys Adjustable/Removable 14 Gun Rack. Temperature and humidity gauges to monitor storage conditions Scratch Resistant Powder Coat Finish Predrilled Mounting Holes. Mounting Kit with Bolts Included. 5th Steel 1" Diameter Locking Bolts. Sturdy Open/Close Spindle Handle. Carpeted Interior & Floor Durable Steel construction 59.1" H x 22.8" W x 19.7" D</p>		
<p>3.) One (1) unit of Enlarger with Lens Kit Specifications: <i>Maximum Film Size: 35mm, 6 x 7cm via optional accessory</i> <i>Maximum Height: 39.5" / 1m</i> <i>Baseboard Size: 19 x 14" / 48.3 x 35.6cm</i> <i>Maximum Print Size on Baseboard: Approx. 11 x 14" / 27.9 x 35.6cm</i> <i>Reversible Column: Yes</i> <i>Light Source: Condenser</i> <i>Replacement Lamp: PH 140</i> <i>Voltage: 120VAC</i> <i>Filter Drawer: Yes, for 3.5 x 3.5" / 8.9 x 8.9cm Filters</i> <i>Modular Head System: 67 VC-W</i> <i>Variable Contrast Head Dichro 67 Colorhead.</i></p> <p>Offer: ENLARGER WITH BASEBOARD AND 50MM LENS KIT AND STEP-DOWN TRANSFORMER Brand: BESELER PRINTMAKER 35 CONDENSER ENLARGER WITH LENS KIT Maximum Film Size 35 mm 6 x 7 cm (via Optional Accessory) Maximum Height 39.5" / 1 m; Baseboard Size 19 x 14" / 48.3 x 35.6 cm Maximum Print Size on Baseboard</p>	<p>Php 135,000.00</p>	<p>One Hundred Thirty-Five Thousand Pesos</p>



<p><i>Approx. 11 x 14" / 27.9 x 35.6 cm</i> Light Source: Condenser, Replacement Lamp PH 1400, Voltage 230 VAC Voltage Stabilized: No, Filter Drawer Yes, for 3.5 x 3.5" / 8.9 x 8.9 cm Filters Modular Head System: 67 VC-W Variable Contrast Head Dichro 67 Colorhead</p>		
<p>4.) One (1) unit of Folding Polygraph Examination Chair Specifications: <i>Material: The chair is made of high-quality aluminum alloy, which is strong and durable but also lightweight and portable. The seat and backrest are made of a comfortable and breathable material, such as mesh or vinyl.</i> <i>Size: The chair is large and comfortable enough to accommodate most people. It has a wide seat and backrest, and a high backrest that provides support for your neck and back.</i></p> <p>. Portable chair can be folded with or without the padded arm attached . Rated to Support 400 lbs . Double Layer of 600 D strain resistant fabric . Weight: at least 20 lbs . Dimensions: H33" W22" D13"</p> <p>Feature: . Easy Adjustment to raise or lower the arm cushion or arm height position is adjusted by moving the padded arm . Cushion inward toward the body or outward away from the body . Allow the arm cushion be angled to obtain the most stable cardio tracing.</p> <p>Features: The chair has several features that make it ideal for use in a polygraph exam, such as: . A built-in armrest with a writing surface</p>	<p>Php 64,500.00</p>	<p>Sixty-Four Thousand Five Hundred Pesos</p>



. A footrest
 . A strap to secure the examinee to the chair
 . A polygraph machine attachment
 . The chair is foldable, which makes it easy to store and transport.
 . The chair is adjustable, so you can customize it to your own comfort level.
 . The chair comes with a warranty, so you can be sure that it is a well-made product

Offer: FOLDING POLYGRAPH EXAMINATION CHAIR
The chair is large and comfortable enough to accommodate most people
Wide seat and backrest, and a high backrest that provides support for neck and back
Portable chair can be folded with or without the padded arm attached
Rated Support 400 lbs
Double layer of 600D strain resitant fabric
Weight: at least 20 lbs
Dimensions: H33" x W22" x D13" Made of High-quality aluminum alloy
Strong and durable, also lightweight and portable
The seat and backrest are made of a comfortable and breathable material, such as mesh or vinyl
Easy Adjustment to raise or lower the arm cushion or arm height position is adjusted by moving the padded arm
Cushion inward toward the body or outward away from the body
Allow the arm cushion be angled to obtain the most stable cardio tracing
Has the following:
A built-in armrest with a writing surface
A footrest
A strap to secure the examinee to the chair
A polygraph machine attachment
1 year warranty



<p>5.) One (1) unit of Fingerprint Digital Scanner kit <i>Specifications:</i> <i>Kit Contents:</i> <i>. 1x Master carrying case (17"L x 12"W x 7"H)</i> <i>. 1x 8oz fingerprint ridge builder pump spray</i> <i>. 4x 2oz jars of tissue builder solution ITEM NO. ITEM</i> REMARKS/RECOMMENDATION <i>pad inking tool; 1ea. Postmortem cardholder;</i> <i>50ea. right hand postmortem cards, 50ea. left hand postmortem cards; 40ea ink remover towelettes; 20ea. nitrile barrier gloves;</i> <i>1ea. kit instruction sheet</i> <i>. 5x 6cc disposable syringes</i> <i>. 5x 18g x 1½" needles</i> <i>. 1x Postmortem pad inking tool</i> <i>. 1x Postmortem cardholder</i> <i>. 50x Right hand postmortem cards</i> <i>. 50x Left hand postmortem cards</i> <i>. 40x Ink remover towelettes</i> <i>. 20x Nitrile barrier gloves</i> <i>. 1x Kit instruction sheet</i> <i>. Pixel Resolution: 512 dpi (average x, y over the scan area)</i> <i>. Scan capture area: 14.6 mm (nom. Width at the center) 18.1 mm (nom. Length)</i> <i>. Reader Size: approx. 65mmx36mmx15.56mm</i> To Include: <i>. 1pc 8oz fingerprint ridge builder pump spray;</i> <i>. 4 bottles 2oz jars tissue builder solution;</i> <i>. 5pcs. 6cc disposable syringes;</i> <i>. 5 pcs. 18g x 1½" needles;</i> <i>. 1pc. Postmortem pad inking tool;</i> <i>. 1pc. Postmortem cardholder;</i> <i>. 50pcs. right hand postmortem cards,</i> <i>. 50pcs. left hand postmortem cards;</i></p>	<p>Php 49,500.00</p>	<p>Forty-Nine Thousand Five Hundred Pesos</p>
--	----------------------	---



<p>. 40pcs. ink remover towelettes; . 20pcs. nitrile barrier gloves; . 1pc. kit instruction sheet . With a Carrying Case</p> <p>Offer: Model: MASTER POTMORTEM FINGER PRINTING KIT Kit Components 1 ea. Master Carrying Case, 17” L x 12” W x 7” H 1 ea. 8 oz. Fingerprint Ridge Builder Pump Spray 4 ea. 2 oz. Jars Tissue Builder Solution 5 ea. 6 cc Disposable Syringes 5 ea. 18 g x 1½” Needles 1 ea. Postmortem Porelon® Pad Inking Tool 1 ea. Postmortem Cardholder 50 ea. Right Hand Postmortem Cards 50 ea. Left Hand Postmortem Cards 40 ea. Ink Remover Towelet 20 ea. Nitrile Barrier Gloves 1 ea. Kit Instruction Sheet</p> <p>Key Features: HID DigitalPersona 4500 Reader Blue LED, Small form factor, Excellent image quality Encrypted fingerprint data, Latent print rejection Works well with dry, moist, or rough fingerprints Compatible with DigitalPersona SDKs for Windows, Linux and Android Rotation invariant, Rugged Applications: Desktop PC Security Mobile PC Security Custom applications Technology: Optical fingerprint Scanning Output image resolution: 512 dpi/ 8-bit grayscale (256 gray levels) Scan Capture Area: 14.6mm (nom. Width); 18.1mm</p>		
<p>6.) One (1) unit of STEREOSCOPIC MICROSCOPE Specifications: . Eyepiece: Pair of WF10x/20 mm with eyecups</p>	<p>Php 65,000.00</p>	<p>Sixty-Five Thousand Pesos</p>



. Head: Binocular or trinocular
 45° inclined tubes, diopter
 adjustment on both eyepieces,
 . Interpupillary distance adjustable
 between 55mm and 75mm
 . Trinocular head is supplied with a
 fixed light path beam splitter
 (50:50)
 . All optics are anti-fungus treated
 and anti-reflection coated for
 maximum light throughput
 . With Dual Magnification
 . Nosepiece with dual 1x/3x or
 2x/4x revolving objectives
 . Magnifications 10x/30x or
 20x/40x (can be enlarged to 135x)
 . Field of view 20mm/6.6mm or
 10mm/5mm,
 . working distance 100mm
 . Zoom Models: Stereo Zoom 0.7x
 to 4.5x parfocal objective
 . Magnification from 7x to 45x,
 field of view 28.5mm to 4.4mm,
 . Working distance 100mm
 . Stands: The rack & pinion and
 pillar stands are equipped with
 ergonomically designed flat bases,
 complete with two object clamps
 and Ø 60mm transparent and
 black/white stage plate
 . Coarse adjustment is equipped
 with tension control
 . Stands are alloy metal casted
 with hardened coating
 . Illumination: 3W transmitted
 and incident LED illuminators
 which can be used simultaneously
 or adjusted separately

**Offer: BRAND: EUROMEX
 STEAREOBLUE
 STEREOSCOPIC MICROSCOPE
 TECHNICAL
 SPECIFICATIONS:
 EYEPIECES
 Pair of WF10x/21 mm secured
 eyepieces supplied with eyecups
 HEAD**

- Binocular or trinocular 45°
 inclined tubes
- Diopter adjustment on both
 eyepieces, except the models
SB.1302-





<p><i>P/1402-P and SB.1302 /1402, which have diopter adjustment on one side</i></p> <ul style="list-style-type: none"> • <i>Interpupillary distance adjustable between 55 mm and 75 mm</i> • <i>Trinocular head is supplied with a fixed light path beamsplitter (50:50)</i> <p><i>All optics are anti-fungus treated and anti-reflection coated for maximum light Throughput</i></p> <p>DUAL MAGNIFICATION MODELS</p> <ul style="list-style-type: none"> • <i>Nosepiece with dual 1x/3x or 2x/4x revolving objectives</i> • <i>Magnifications 10x/30x or 20x/40x (can be enlarged to 135x)</i> • <i>Field of view 21 mm/6.9 mm or 10.5 mm/5.2 mm</i> • <i>Working distance 100 mm</i> <p>ZOOM OBJECTIVES PARFOCAL</p> <p><i>Zoom range Magnification Field of view Working distance</i></p> <p><i>0.7x to 4.5x 7x to 45x 29.9 mm to 4.6 mm 100 mm</i></p> <p><i>0.5x to 5.5x (EVO) 5x to 55x 38 mm to 3.9 mm 100 mm</i></p>		
<p>7.) One (1) unit of Fuming Chamber (Capture BT)</p> <p><i>Specifications:</i></p> <p><i>Interior:</i></p> <ul style="list-style-type: none"> <i>Type 304 brushed stainless-steel interior with removable perforated floor</i> <i>. Four stainless steel hanging rods (26.9" long x 3/8" dia)</i> <i>. Quick-release sidewall brackets mounted at four heights</i> <i>. Interior space of 19 cubic feet and 58.6" diagonal dimension</i> <i>. Built-in humidifier and compartment with 500mL water bottle</i> <i>. Built-in CA fuming compartment with heater plate</i> <i>. Tempered safety glass door with electronic door lock to prevent opening during the fuming cycle</i> <i>. Power outage override</i> <i>. Interior LED light for illumination</i> 	<p>Php 2,395,000.00</p>	<p>Two Million Three Hundred Ninety-Five Thousand Pesos</p>



. 30-minute end-of-fuming-cycle alert

. ECM recirculation blower

Exterior:

. Powder-coated steel exterior

Controls:

. Full-color, eye-level LCD control screen for display of programs

. Program parameters

. Number of completed fuming cycles

. Filter life remaining

. Low-level water reservoir and open-door alerts

. Microprocessor-controlled operating system

Operating Parameters:

. Chamber humidity: 80% ±5% relative humidity

. Pre-fuming humidity incubation

. Fuming temperature: 424°F within ±1%

. Fuming and exhaust times

Additional Features:

. Stores 20 programs

. Includes 3 factory set programs: Low Heat, High Heat, Lumincyano

. Includes diagnostic mode with audible/visual alerts for program cycle completion

. Acti-Vent Smart Controls with programmable purge time

. Standby exhaust mode

. Cleaning mode

. Drawer: 28"W x 13" D x 1.5" H (71 x 33 x 4cm) with flush-mounted disappearing handle and 5" x 6" platform

. One each Prefilter, Carbon Filter, and Humidifier Filter are included and accessible from inside the chamber

. Four leveling feet

. 10' (3meter) power cord and plug

Certifications:

. ETL and ETL-C listed

. CE conformity marking

Offer: Capture Benchtop Fuming Chambers

All models include:



- *Type 304 brushed stainless-steel interior with removeable perforated floor, four stainless steel hanging rods (26.9" long x 3/8" dia.) and quick-release sidewall brackets at four heights*
- *Powder-coated steel exterior*
- *Interior space of 19 cubic feet and 58.6" diagonal dimension*
- *Built-in humidifier and compartment with 500 ml water bottle*
- *Full-color, eye-level LCD control screen for display of programs, program parameters, number of completed fuming cycles, filter life remaining, low-level water reservoir and open-door alerts*
- *Microprocessor-controlled operating system for adjustment of chamber humidity to 80% ± 5% relative humidity, pre-fuming humidity incubation, fuming temperature up to 424° F (218° C) within ± 1%, and fuming and exhaust times. Stores 20 programs. Includes 3 factory set programs: Low Heat, High Heat, Lumicyano. Includes diagnostic mode with audible/visual alerts for program cycle completion*
- *One each prefilter, carbon filter and humidifier filter are accessible from inside the chamber*
- *Built-in CA fuming compartment with heater plate*
- *Tempered safety glass door with electronic door lock to prevent opening during fuming cycle. Includes power outage override*
- *Interior LED light for illumination and 30-minute end-of-fuming-cycle alert*
- *ECM recirculation blower*
- *Exhaust blower*
- *Acti-Vent™ Smart Controls with programmable purge time, standby exhaust mode and cleaning mode*
- *Drawer, 28.0" w x 13.0" d x 1.5" h with flush-mounted disappearing handle and 5.0" x 6.0" platform*





Republic of the Philippines
WESTERN MINDANAO STATE UNIVERSITY
OFFICE OF THE PRESIDENT
 Normal Road, Baliwasan Zamboanga City
 Telefax.: 062-992-3084
www.wmsu.edu.ph



<ul style="list-style-type: none"> • <i>Four leveling feet, 10' power cord and plug</i> • <i>Shipping weight 480 lbs. (218 kg)</i> <i>Standards conformance & regulations:</i> <ul style="list-style-type: none"> • <i>CAN/CSA C22.2 No. 61010-1 (115V, 60 Hz models)</i> • <i>CE Conformity marking (230V, 50/60 Hz models)</i> • <i>ETL Listed (115V/230V, 50/60Hz models)</i> • <i>UL 61010-1 (115V/230V, 50/60 Hz models) Options include:</i> <ul style="list-style-type: none"> • <i>Region-specific electrical configurations</i> • <i>All models require (not included):</i> <ul style="list-style-type: none"> • <i>Super glue</i> • <i>Fuming dishes, • Purified water</i> 		
TOTAL CONTRACT PRICE	Php 3,009,000.00	Three Million Nine Thousand Pesos Only

You are hereby required to provide, within ten (10) days from receipt hereof, the Performance Security/ Performance Bond equivalent to the following;

Form of Performance Security	Amount of Performance Security (Equal to Percentage of the Total Contract Price)
a) Cash or cashier's/manager's check issued by a Universal or Commercial Bank.	Five percent (5%)
b) Bank draft/ guarantee or irrevocable letter of credit issued by a Universal or Commercial Bank: Provided, however, that it shall be confirmed or authenticated by a Universal or Commercial Bank, if issued by a foreign bank	Five percent (5%)
c) Surety bond callable upon demand issued by a surety or insurance company duly certified by the insurance Commission as authorized to issue such security.	Thirty percent (30%)
d) Any combination of the foregoing.	Proportionate to share of form with respect to total amount of security

Failure to provide the Performance Security shall constitute sufficient ground for the cancellation of the award and forfeiture of the Bid Security.

Very truly yours,

MA. CARLA A. OCHOTORENA, RN., Ph.D.
 President

Received by:

 (Signature Over Printed Name)

Date: _____