



NOTICE OF AWARD

MAR 06 2024

PRO MAINTTECH CONSULTANCY, INC.
 BLK 9, LOT 14 MAYA ST., CAMELLA HOMES ALABANG,
 MUNTINLUPA CITY

Madam/Sir:

This is to advise you that your bid dated December 12, 2023 for PR 23-10-479; Public Bidding Procurement of Supply and Delivery of Various Laboratory Supplies, Materials and Equipment for the College of Agriculture, with a following Contract Price is hereby accepted;

Object of Bidding	Total Amount in Figures	Amount in Words
<p>3.) One (1) unit of DIGITAL COLORIMETER <i>Specifications:</i> . Accuracy: $\pm 0.05A$ at 1A . Wavelength Range: 400 to 700nm . Height (Metric): 60mm . Photometric Repeatability: ± 0.02 A at 1A . Resolution: 0.02 at 1 A (Absorbance), 2% (Transmission) . Spectra Bandwidth: 40nm . Voltage: 240V . Electrical Requirements: 240V, 50/60Hz . Transmission Range: 0 to 199% . Width (Metric): 146mm <i>To include Accessories:</i> . Plastic and Glass Cuvette . Color Reference Standards, can be used to solid and liquid - with On Site Training <i>Key Feature:</i> -Advance from visual to electronic color measurement with confidence -Interpret result easily with visual color comparison mode and direct digital reading -Obtain quality checks with the on-screen warning system-results displayed in green, yellow and red</p>	<p>Php 418,000.00</p>	<p>Four Hundred Eighteen Thousand Pesos</p>



<p><i>-Easily set time, date, preferences, and projects through the intuitive touch screen</i></p> <p><i>-Save 20,000 individual readings to the internal memory</i></p> <p><i>-Internationally recognized industry standards</i></p> <p>Offer: Model; BCM-110/BCM-200</p> <p>Illuminating/Viewing Geometry: 8/d</p> <p>Measuring Aperture: ϕ4mm; ϕ8mm</p> <p>Detector: Silicon photoelectric diode</p> <p>Light Source Device: LED blue light excitation</p> <p>Display: TFT LCD</p> <p>Errors Between Each Equipment: $\leq 0.80\Delta E^*ab$; $\leq 0.50\Delta E^*ab$</p> <p>Storage: 100pcs standards, 20000pcs samples; 100pcs standards, 20000pcs samples</p> <p>Repeatability: Standard deviation within ΔE^*ab 0.08 Average of 30 measurements of standard white plate</p> <p>lamp Life: 3 years, more than 1 million time; 5 years, more than 1.6 million time</p> <p>Charging Time: 8 hours-100% electricity; 2 hours (8 hours for first charge)-100% electricity</p> <p>Measurement Times Before Recharging: 3000 times in 8 hours</p> <p>Ambient Temp./Humidity Range: -10~40°C, relative humidity 0-85% without condensation</p> <p>Data Interface: USB</p> <p>Optional Accessory: Miniature thermal printer, Powder test box</p> <p>Universal Test Components, Powder test box, Miniature thermal printer</p>		
<p>5.) Two (2) unit of SAFETY CHEMICAL STORAGE SHELF/CABINET</p> <p>Specifications:</p> <p>. External dimensions (mm): 470x1800x900</p>	<p>Php 200,000.00</p>	<p>Two Hundred Thousand Pesos</p>



<p>. Inner dimensions (mm): 440x860x260 (x3 stages); 860x440x382 (x2 stages) . Main unit material: 20mm thick particle board, surface: plywood (antibacterial), Cosmetic board with rails/steel . Shelf load tolerance: Fixed shelf/30 Kg, rail shelf/20kg . Mm Tana: 260, 382, pitch . Drawer: 430mm (slide rail shelf) . Weight: at least 81kg To include the ff. Accessories: . Drug tray: 9 pieces . Consolidated metal bracket: bolt x 2 pieces . Fixed metal bracket: L metal bracket x 2 pieces</p>		
<p>12.) Two (2) unit of SOIL MOISTURE TESTER/METER . Specifications: . Sensor Type: PIN . Content Analyzer/Range: 0~80% . Digital Display: LCD . Restore: 99 groups of measurements . Accuracy: $\pm (0.5\% n+1)$ or higher . Resolution: 0.1 . Condition Temp.: 0~500C . Humidity: <90% RH . Power Supply: 4 x 1.5 V . Statistical Available: Last Value/Mean Value/Max Value, Min Value/Number of Readings Offer: Brand: Digital Instrument Model: MC-72828Soil Origin: Taiwan Sensor Type: Pin Range: 0-80% Accuracy: $\pm (0.5\% n-1)$ Resolution: 0.1 Display: LCD Led Indicator: Green LED represents a safe, air-dry state; Yellow LED represents a borderline state The Statistics Available: Last Value/Mean Value/ Max Value/Min. Value/Number of Readings Memory: 99 groups Operating Temperature: 0-50°C</p>	<p>Php 20,000.00</p>	<p>Ten Thousand Pesos</p>

M



<p>Conditions Humidity: <90% R11 Power Supply: 4x1.5V AAA (UM 4) Battery Dimensions: Main Unit: 140x73x35mm Sensor: 320x44x44mm Length of Pin: 150mm Diameter of pin: 3mm Distance between 2 pins: 18mm Standard Accessories: Main Unit, Sensor, Carrying Case (B04), Operating Manual Optional Accessories: USB Data Cable with Software; Bluetooth Data Adapter with Software</p>		
<p>14.) Four (4) unit of SOIL PARAMETER SENSOR SET Compose of the ff. sensors:</p> <ul style="list-style-type: none"> . Soil Nitrogen Concentration Sensor . Soil Phosphorus Concentration Sensor . Soil Potassium Concentration Sensor . Range: 1-999mg/kg . ±2% F.S. <p>Offer: Soil nitrogen, phosphorous, potassium three-in-one fertility sensor (Type 485) Model: RS-NPK-N01-TR Brand: Shandong Renke Control Technology Co. LTD Origin: China Technical Specs: DC Powered: DC 5-30V Maximum power consumptions: ≤0.15W (@12V DC, 25 °C) Operating Temperature: 0 °C ` 55 °C NPK Parameters: Range: 1-1999 mg/kg (mg/L) Resolution: 1 mg/kg (mg/L) Precision: ± 2%FS Response Time: <1S Protection Class: IP68 Probe Material: Stainless Steel Sealing: Black flame-retardant epoxy resin Default Cable length: 2 meters, cable length can be customized Dimensions: 45*15*123mm Output Signal: RS485 (Modbus protocol)</p>	<p>Php 60,000.00</p>	<p>Sixty Thousand Pesos</p>



<p>16.) Four (4) unit of LABORATORY STAINLESS CART</p> <p><i>Specifications:</i></p> <ul style="list-style-type: none"> . Material: Solid Stainless Steel . Capacity: At least 700lbs . Dimension: 24"W x 26"L x 36"H . Layers: 3 . With Handle <p><i>Offer: Model: Local Fabrication</i> Brand: EOM Origin: Philippines Solid Stainless Steel Capacity: At least 700lbs Dimension: 24" W x 26" L x 35 "H Layers: 3 with Stainless steel tube upright support and handle, Rubber Caster Wheel, 2 w/brake, 2 non brake</p> <p><i>Specification & Features:</i> High Quality and brand new 3 layers trolley cart Lightweight and portable Four universal wheels 2 w/brake, 2 non-brake for easy moving Good for Clinic, Hospital, Laboratory</p>	<p>Php 59,000.00</p>	<p>Fifty-Nine Thousand Pesos</p>
<p>17.) Two (2) unit of UV STERILIZATION CABINET</p> <p><i>Specifications:</i></p> <ul style="list-style-type: none"> . Type: with Ozone . UV Ray Wavelength: 253.7/184.9nm . Sterilization Way: 2 sides of UV ray+1 side of Ozone . Capacity: 200L . Power: 120W . UV Lamp Materials: Quartz glass . Shelves: Standard 2pc. can be optional . Internal Size: at least 518x523x778mm . External Size: at least 750x663x1200mm <p><i>Offer: Model: BJPX-SV0200</i> Brand: BIOBASE Origin: China Technical Parameters : Type: with Ozone</p>	<p>Php 110,000.00</p>	<p>One Hundred Ten Thousand Pesos</p>

M



Republic of the Philippines
WESTERN MINDANAO STATE UNIVERSITY
OFFICE OF THE PRESIDENT
 Normal Road, Baliwasan Zamboanga City
 Telefax.: 062-992-3084
www.wmsu.edu.ph



<p> UV Ray Wavelength 253.7/184.9mm Sterilization Way: 2 sides of UV ray+1 side of ozone Capacity: 200 L Power: 120 W UV Lamp Material: Quartz Glass Shelves: Standard 2pc, can be optional Internal Size (mm): 518*523*778 External Size (mm): 750*663*1200 Packing Size (mm): 875*788*1265 Gross Weight (kg): 100 </p>		
<p> 19.) Four (4) unit of PORTABLE TEMPERATURE AND HUMIDITY DATA LOGGER Specifications: <i>. Temp. Range: -40-degree celcius~85-degree celcius</i> <i>. Humidity Range: 0~100%RH</i> <i>. Temperature Accuracy: 0.5</i> <i>. Humidity Accuracy: 3%RH</i> <i>. Temperature Resolution: 0.1oC</i> <i>. Humidity Resolution: 3%RH</i> <i>. Recording capacity: 16000 points (MAX).</i> Offer: Model: SITH-06 Brand: SENSE Instruments Origin: China Features: <ul style="list-style-type: none"> • Wide 3.9-inch LCD screen with Backlight function • Touch-sensitive buttons • Key lock feature • Low Battery indicator • Time (Clock) display • HI/LOW limit indication • MAX/MIN/AVG display • Record Function via unit • Large storage capacity • Xt/csv/xls/dlg files are available </p>	<p> Php 30,000.00 </p>	<p> Thirty Thousand Pesos </p>
<p> TTAL CONTRACT PRICE </p>	<p> Php 897,000.00 </p>	<p> Eight Hundred Ninety-Seven Thousand Pesos Only </p>

You are hereby required to provide, within ten (10) days from receipt hereof, the Performance Security/ Performance Bond equivalent to the following;

Form of Performance Security	Amount of Performance Security (Equal to
------------------------------	--

M



Republic of the Philippines
WESTERN MINDANAO STATE UNIVERSITY
OFFICE OF THE PRESIDENT
 Normal Road, Baliwasan Zamboanga City
 Telefax.: 062-992-3084
www.wmsu.edu.ph



	Percentage of the Total Contract Price
a) Cash or cashier's/manager's check issued by a Universal or Commercial Bank.	Five percent (5%)
b) Bank draft/ guarantee or irrevocable letter of credit issued by a Universal or Commercial Bank: Provided, however, that it shall be confirmed or authenticated by a Universal or Commercial Bank, if issued by a foreign bank	Five percent (5%)
c) Surety bond callable upon demand issued by a surety or insurance company duly certified by the insurance Commission as authorized to issue such security.	Thirty percent (30%)
d) Any combination of the foregoing.	Proportionate to share of form with respect to total amount of security

Failure to provide the Performance Security shall constitute sufficient ground for the cancellation of the award and forfeiture of the Bid Security.

Very truly yours,

MA. CARLA A. OCHOTORENA, RN., Ph.D.
 President

Received by:

 (Signature Over Printed Name)

Date: _____

M