



NOTICE OF AWARD

MAR 06 2024

NOVEAULAB ASIA CORP.

Unit SS 105 DSL Bldg., 380 Del Monte Avenue,
 Quezon City, Metro Manila

Sir/Madam:

This is to advise you that your bid dated December 28, 2023 for PR-23-10-520; Public Bidding Procurement of Supply and Delivery of Various Laboratory Equipment for the College of Agriculture of the University, with a following Contract Price is hereby accepted;

Object of Bidding	Total Amount in Figures	Amount in Words
<p>3.) One (1) unit of CRUDE FIBER ANALYZER</p> <p><i>Specifications:</i></p> <ul style="list-style-type: none"> . Number of Sample: Up to 6 samples . Capacity Per Day: <ul style="list-style-type: none"> ? Up to 36 (Crude Fiber/Wendee Method) ? Up to 60 (Other Methods) . Sample Quantity: From 0.5 to 3g . Display: 7" color touch screen . Measurement Range: 0.1-100% . Repeatability: ±% relative at 5%-30% fiber amount . Lighting: LED . Level of Automation: Fully Automated . Heating and Dispensing of Reagents: Automatic . Reagent Pre-Heating Time: at least 5-7 min . Time from Preheated Temperature to boiling: at least 5-10 min . Connectivity: Cloud via LAN or USB WiFi adapter . Interfaces: 3 x USB (Balance, Barcode scanner, mouse, USB Stick, USB Wi-Fi Adapter), Ethernet (PC) . Result Calculation: Automatic, On-board archive for data storage . Water Consumption: from 1.01 min <p>WITH ON-SITE TRAINING</p> <p>Offer: HANON F800 Fiber Analyzer with F800-B Cold Extractor</p>	<p>Php 675,351.00</p>	<p>Six Hundred Seventy-Five Thousand Three Hundred Fifty-One Pesos</p>



Republic of the Philippines
WESTERN MINDANAO STATE UNIVERSITY
OFFICE OF THE PRESIDENT

Normal Road, Baliwasan Zamboanga City
 Telephone: 062-992-3084
www.wmsu.edu.ph



<p>Measurement range: 0.1% ~100% Sample weight: 0.5g ~3g Repeatability error: Craw Fiber Content below 10%, ≤0.4% Craw Fiber Content above 10%, ≤1% Capacity: 6 pcs/batch Pre-heating time: 10-12min Heating to boiling: 13-15min Display: 7 inches touch color screen Rated power: 2.2KW Power supply: 220 VAC ±10% 50Hz WITH ON-SITE TRAINING</p>		
<p>5.) One (1) unit of AUTOCLAVE MACHINE</p> <p><i>Specifications:</i></p> <ul style="list-style-type: none"> . Capacity: 50L . Chamber Size: 386x514mm . Designed Pressure: 0.28Mpa . Designed Temp.: 1340C . Working Pressure: 0.23MPa . Working Temp.: 105~1360C . Temp. Display accuracy: 0.10C . Timing Range: 0~999min . Dynamic Pulse . Exhaust Time (0-9 times) . Dynamic Pulse . Exhaust Temp. (105-136 degrees Celcius) . Temp. Holding Range: 45~600C . Consumption: 4.4KW . Power Supply: 220V/60Hz . Stainless Steel Basket: 1 pc . External Size (WxDXH)mm: 640x550x950mm <p><i>Feature:</i></p> <ul style="list-style-type: none"> . LED screen displays all steps of full process as well as error codes. . Independent quick service window, easy for repairing and maintenance. . Automatic selecting quick or low exhaust to avoid sterilization liquid overflowing. . Sterilization programs for dressings, equipment, rubber, culture medium, waste, etc. . Hand wheel type of quick-open door structure, self-expendable sealing ring, easy operating and safe. . Complete process of filling water, dynamic pulse exhaust, heating, 	<p>Php 211,863.00</p>	<p>Two Hundred Eleven Eight Hundred Sixty-Three Pesos</p>





Republic of the Philippines
WESTERN MINDANAO STATE UNIVERSITY
OFFICE OF THE PRESIDENT

Normal Road, Baliwasan Zamboanga City
 Telephone: 062-992-3084
www.wmsu.edu.ph



<p><i>sterilizing, draining and drying runs automatically.</i></p> <p><i>. Adopting certain temperature (98~1020) exhaust methods and dynamic pulse exhaust methods to empty the cold air inside chamber for ensuring steam saturability.</i></p> <p><i>. Inner stainless steel water tank for water and steam to circulate inside. Steam dose not exhaust during sterilization, so as to keep the outside clean and dry.</i></p> <p>WITH ON-SITE TRAINING</p> <p>Offer: BIOBASE VERTICAL AUTOCLAVE BKQ-B50II Capacity: 50L Chamber Material: S30408 Designed Pressure: 0.28Mpa Designed Temp: 134°C Working Pressure: 0.23MPa Working Temp.: 105~136°C Temp. Display Accuracy: 0.1°C Timing Range: 0~999min Dynamic Pulse/Exhaust Times: 0~9 times Dynamic Pulse/Exhaust Temp:105~136°C Temp. Holding Range: 45~60°C Consumption: 4.4KW Power Supply: AC110/220V±10%, 50/60Hz SS Basket: 1 pc WITH ON-SITE TRAINING</p>		
<p>Place of Delivery: SAN RAMON CAMPUS</p>		
<p>TOTAL CONTRACT PRICE</p>	<p>Php 887,214.00</p>	<p>Eight Hundred Eighty-Seven Thousand Two-Hundred Fourteen Pesos Only</p>


You are hereby required to provide, within ten (10) days from receipt hereof, the Performance Security/ Performance Bond equivalent to the following;

Form of Performance Security	Amount of Performance Security (Equal to Percentage of the Total Contract Price)
a) Cash or cashier's/manager's check issued by a Universal or Commercial Bank.	Five percent (5%)
b) Bank draft/ guarantee or irrevocable letter of credit issued by a Universal or Commercial Bank: Provided, however, that it	Five percent (5%)





Republic of the Philippines
WESTERN MINDANAO STATE UNIVERSITY
OFFICE OF THE PRESIDENT
 Normal Road, Baliwasan Zamboanga City
 Telephone: 062-992-3084
www.wmsu.edu.ph



shall be confirmed or authenticated by a Universal or Commercial Bank, if issued by a foreign bank	
c) Surety bond callable upon demand issued by a surety or insurance company duly certified by the insurance Commission as authorized to issue such security.	Thirty percent (30%)
d) Any combination of the foregoing.	Proportionate to share of form with respect to total amount of security

Failure to provide the Performance Security shall constitute sufficient ground for the cancellation of the award and forfeiture of the Bid Security.

Very truly yours,

MA. CARLA A. OCHOTORENA, RN., Ph.D.
 President

Received by:

 (Signature Over Printed Name)

Date: _____