PHILIPPINE BIDDING DOCUMENTS

(As Harmonized with Development Partners)

Procurement of GOODS

Government of the Republic of the Philippines

Supply and Delivery of Various Laboratory Supplies, Materials and Equipment of the College of Agriculture for the University

(PR 23-10-479)

Sixth Edition July 2020

Preface

These Philippine Bidding Documents (PBDs) for the procurement of Goods through Competitive Bidding have been prepared by the Government of the Philippines for use by any branch, constitutional commission or office, agency, department, bureau, office, or instrumentality of the Government of the Philippines, National Government Agencies, including Government-Owned and/or Controlled Corporations, Government Financing Institutions, State Universities and Colleges, and Local Government Unit. The procedures and practices presented in this document have been developed through broad experience, and are for mandatory use in projects that are financed in whole or in part by the Government of the Philippines or any foreign government/foreign or international financing institution in accordance with the provisions of the 2016 revised Implementing Rules and Regulations of Republic Act No. 9184.

The Bidding Documents shall clearly and adequately define, among others: (i) the objectives, scope, and expected outputs and/or results of the proposed contract or Framework Agreement, as the case may be; (ii) the eligibility requirements of Bidders; (iii) the expected contract or Framework Agreement duration, the estimated quantity in the case of procurement of goods, delivery schedule and/or time frame; and (iv) the obligations, duties, and/or functions of the winning bidder.

Care should be taken to check the relevance of the provisions of the PBDs against the requirements of the specific Goods to be procured. If duplication of a subject is inevitable in other sections of the document prepared by the Procuring Entity, care must be exercised to avoid contradictions between clauses dealing with the same matter.

Moreover, each section is prepared with notes intended only as information for the Procuring Entity or the person drafting the Bidding Documents. They shall not be included in the final documents. The following general directions should be observed when using the documents:

- a. All the documents listed in the Table of Contents are normally required for the procurement of Goods. However, they should be adapted as necessary to the circumstances of the Procurement Project.
- b. Specific details, such as the "name of the Procuring Entity" and "address for bid submission," should be furnished in the Instructions to Bidders, Bid Data Sheet, and Special Conditions of Contract. The final documents should contain neither blank spaces nor options.
- c. This Preface and the footnotes or notes in italics included in the Invitation to Bid, Bid Data Sheet, General Conditions of Contract, Special Conditions of Contract, Schedule of Requirements, and Specifications are not part of the text of the final document, although they contain instructions that the Procuring Entity should strictly follow.
- d. The cover should be modified as required to identify the Bidding Documents as to the Procurement Project, Project Identification Number, and Procuring Entity, in addition to the date of issue.
- e. Modifications for specific Procurement Project details should be provided in the Special Conditions of Contract as amendments to the Conditions of Contract. For easy completion, whenever reference has to be made to specific clauses in the Bid Data Sheet or Special Conditions of Contract, these terms

- shall be printed in bold typeface on Sections I (Instructions to Bidders) and III (General Conditions of Contract), respectively.
- f. For guidelines on the use of Bidding Forms and the procurement of Foreign-Assisted Projects, these will be covered by a separate issuance of the Government Procurement Policy Board.

Table of Contents

Glossa	ry of Acronyms, Terms, and Abbreviations	4
Section	n I. Invitation to Bid	7
Section	n II. Instructions to Bidders	10
1.	Scope of Bid	
2.	Funding Information	11
3.	Bidding Requirements	11
4.	Corrupt, Fraudulent, Collusive, and Coercive Practices	11
5.	Eligible Bidders	11
6.	Origin of Goods	12
7.	Subcontracts	12
8.	Pre-Bid Conference	12
9.	Clarification and Amendment of Bidding Documents	12
10.	Documents comprising the Bid: Eligibility and Technical Components	13
11.	Documents comprising the Bid: Financial Component	13
12.	Bid Prices	13
13.	Bid and Payment Currencies	14
14.	Bid Security	14
15.	Sealing and Marking of Bids	14
16.	Deadline for Submission of Bids	15
17.	Opening and Preliminary Examination of Bids	15
18.	Domestic Preference	15
19.	Detailed Evaluation and Comparison of Bids	15
20.	Post-Qualification	16
21.	Signing of the Contract	16
Section	n III. Bid Data Sheet	17
Section	n IV. General Conditions of Contract	25
1.	Scope of Contract	26
2.	Advance Payment and Terms of Payment	26
3.	Performance Security	26
4.	Inspection and Tests	26
5.	Warranty	27
6.	Liability of the Supplier	27
Section	n V. Special Conditions of Contract	28
	n VI. Schedule of Requirements	
	n VII. Technical Specifications	
	n VIII. Checklist of Technical and Financial Documents	

Glossary of Acronyms, Terms, and Abbreviations

ABC - Approved Budget for the Contract.

BAC – Bids and Awards Committee.

Bid – A signed offer or proposal to undertake a contract submitted by a bidder in response to and in consonance with the requirements of the bidding documents. Also referred to as *Proposal* and *Tender*. (2016 revised IRR, Section 5[c])

Bidder – Refers to a contractor, manufacturer, supplier, distributor and/or consultant who submits a bid in response to the requirements of the Bidding Documents. (2016 revised IRR, Section 5[d])

Bidding Documents – The documents issued by the Procuring Entity as the bases for bids, furnishing all information necessary for a prospective bidder to prepare a bid for the Goods, Infrastructure Projects, and/or Consulting Services required by the Procuring Entity. (2016 revised IRR, Section 5[e])

BIR – Bureau of Internal Revenue.

BSP – Bangko Sentral ng Pilipinas.

Consulting Services – Refer to services for Infrastructure Projects and other types of projects or activities of the GOP requiring adequate external technical and professional expertise that are beyond the capability and/or capacity of the GOP to undertake such as, but not limited to: (i) advisory and review services; (ii) pre-investment or feasibility studies; (iii) design; (iv) construction supervision; (v) management and related services; and (vi) other technical services or special studies. (2016 revised IRR, Section 5[i])

CDA - Cooperative Development Authority.

Contract – Refers to the agreement entered into between the Procuring Entity and the Supplier or Manufacturer or Distributor or Service Provider for procurement of Goods and Services; Contractor for Procurement of Infrastructure Projects; or Consultant or Consulting Firm for Procurement of Consulting Services; as the case may be, as recorded in the Contract Form signed by the parties, including all attachments and appendices thereto and all documents incorporated by reference therein.

CIF – Cost Insurance and Freight.

CIP – Carriage and Insurance Paid.

CPI – Consumer Price Index.

DDP – Refers to the quoted price of the Goods, which means "delivered duty paid."

DTI – Department of Trade and Industry.

EXW – Ex works.

FCA - "Free Carrier" shipping point.

FOB – "Free on Board" shipping point.

Foreign-funded Procurement or Foreign-Assisted Project-Refers to procurement whose funding source is from a foreign government, foreign or international financing institution as specified in the Treaty or International or Executive Agreement. (2016 revised IRR, Section 5[b]).

Framework Agreement – Refers to a written agreement between a procuring entity and a supplier or service provider that identifies the terms and conditions, under which specific purchases, otherwise known as "Call-Offs," are made for the duration of the agreement. It is in the nature of an option contract between the procuring entity and the bidder(s) granting the procuring entity the option to either place an order for any of the goods or services identified in the Framework Agreement List or not buy at all, within a minimum period of one (1) year to a maximum period of three (3) years. (GPPB Resolution No. 27-2019)

GFI – Government Financial Institution.

GOCC –Government-owned and/or –controlled corporation.

Goods - Refer to all items, supplies, materials and general support services, except Consulting Services and Infrastructure Projects, which may be needed in the transaction of public businesses or in the pursuit of any government undertaking, project or activity, whether in the nature of equipment, furniture, stationery, materials for construction, or personal property of any kind, including non-personal or contractual services such as the repair and maintenance of equipment and furniture, as well as trucking, hauling, janitorial, security, and related or analogous services, as well as procurement of materials and supplies provided by the Procuring Entity for such services. The term "related" or "analogous services" shall include, but is not limited to, lease or purchase of office space, media advertisements, health maintenance services, and other services essential to the operation of the Procuring Entity. (2016 revised IRR, Section 5[r])

GOP – Government of the Philippines.

GPPB –Government Procurement Policy Board.

INCOTERMS – International Commercial Terms.

Infrastructure Projects – Include the construction, improvement, rehabilitation, demolition, repair, restoration or maintenance of roads and bridges, railways, airports, seaports, communication facilities, civil works components of information technology projects, irrigation, flood control and drainage, water supply, sanitation, sewerage and solid waste management systems, shore protection, energy/power and electrification facilities, national buildings, school buildings, hospital buildings, and other related construction projects of the government. Also referred to as civil works or works. (2016 revised IRR, Section 5[u])

LGUs – Local Government Units.

NFCC – Net Financial Contracting Capacity.

NGA – National Government Agency.

PhilGEPS - Philippine Government Electronic Procurement System.

Procurement Project – refers to a specific or identified procurement covering goods, infrastructure project or consulting services. A Procurement Project shall be described, detailed, and scheduled in the Project Procurement Management Plan prepared by the agency which shall be consolidated in the procuring entity's Annual Procurement Plan. (GPPB Circular No. 06-2019 dated 17 July 2019)

PSA – Philippine Statistics Authority.

SEC – Securities and Exchange Commission.

SLCC – Single Largest Completed Contract.

Supplier – refers to a citizen, or any corporate body or commercial company duly organized and registered under the laws where it is established, habitually established in business and engaged in the manufacture or sale of the merchandise or performance of the general services covered by his bid. (Item 3.8 of GPPB Resolution No. 13-2019, dated 23 May 2019). Supplier as used in these Bidding Documents may likewise refer to a distributor, manufacturer, contractor, or consultant.

UN – United Nations.

Section I. Invitation to Bid

Notes on the Invitation to Bid

The Invitation to Bid (IB) provides information that enables potential Bidders to decide whether to participate in the procurement at hand. The IB shall be posted in accordance with Section 21.2 of the 2016 revised IRR of RA No. 9184.

Apart from the essential items listed in the Bidding Documents, the IB should also indicate the following:

- a. The date of availability of the Bidding Documents, which shall be from the time the IB is first advertised/posted until the deadline for the submission and receipt of bids;
- b. The place where the Bidding Documents may be acquired or the website where it may be downloaded;
- c. The deadline for the submission and receipt of bids; and
- d. Any important bid evaluation criteria (*e.g.*, the application of a margin of preference in bid evaluation).

The IB should be incorporated in the Bidding Documents. The information contained in the IBmust conform to the Bidding Documents and in particular to the relevant information in the Bid Data Sheet.



RepublicofthePhilippines WESTERN MINDANAO STATE UNIVERSITY BIDS AND AWARDS COMMITTEE FOR GOODS



Normal Road, Baliwasan Zamboanga City Telephone: 062-991-7875 www.wmsu.edu.ph

INVITATION TO BID FOR Supply and Delivery of Various Laboratory Supplies, Materials and Equipment of the College of Agriculture for the University (PR 23-10-479)

- 1. The Western Mindanao State University, through the GAA 2023 intends to apply the sum of Three Million Nine Hundred Sixty-Six Thousand pesos (Php 3,966,000.00) being the ABC to payments under the contract for Supply and Delivery of Various Laboratory Supplies, Materials and Equipment of the College of Agriculture for the University. Bids received in excess of the ABC shall be automatically rejected at bid opening.
- 2. The *Western Mindanao State University* now invites bids for the above Procurement Project. Delivery of the Goods is required by *within Thirty (30) calendar days*. Bidders should have completed, within *reasonable period* from the date of submission and receipt of bids, a contract similar to the Project. The description of an eligible bidder is contained in the Bidding Documents, particularly, in Section II (Instructions to Bidders).
- 3. Bidding will be conducted through open competitive bidding procedures using a non-discretionary "pass/fail" criterion as specified in the 2016 Revised Implementing Rules and Regulations (IRR) of Republic Act (RA) No. 9184.
- 4. Prospective Bidders may obtain further information from *WMSU-BAC Office* and inspect the Bidding Documents at the address given below during 8:00 AM to 5:00 PM.
- 5. A complete set of Bidding Documents may be acquired by interested Bidders on *November 22 to December 12, 2023 from* the given address and website(s) and upon payment of the applicable fee for the Bidding Documents, pursuant to the latest Guidelines issued by the GPPB, in the amount of *Five Thousand Pesos* (5,000.00). The Procuring Entity shall allow the bidder to present its proof of payment for the fees will be presented in person, by facsimile, or through electronic means.
- 6. Bids must be duly received by the BAC Secretariat through manual submission at the office address indicated below, on or before *December 12, 2023 at 9:30 AM at the WMSU BAC-Office*. Late bids shall not be accepted.
- 7. The Western Mindanao State University will hold a Pre-Bid Conference¹ on November 29, 20239:30 AM at BAC Office, 2nd Floor Admin. Building, Western Mindanao State University, Baliwasan, Zamboanga City, which shall be open to prospective bidders.
- 8. Bid opening shall be on *December 12, 2023 at 9:30 AM* at the given address. Bids will be opened in the presence of the bidders' representatives who choose to attend the activity.

May be deleted in case the ABC is less than One Million Pesos (PhP1,000,000) where the Procuring Entity may not hold a pre-bid conference.

- 9. The *Western Mindanao State University* reserves the right to reject any and all bids, declare a failure of bidding, or not award the contract at any time prior to contract award in accordance with Sections 35.6 and 41 of the 2016 revised IRR of RA No. 9184, without thereby incurring any liability to the affected bidder or bidders.
- 10. For further information, please refer to:

Ma. Josefina Mendoza Bacalla Head Secretariat for GOODS 2nd Floor Admin. Building Western Mindanao State University Normal Road, Baliwasan Zamboanga City

Tel. No.: (062)991-7875 Email: <u>bac@wmsu</u>.ph

11. You may visit the following websites:

For downloading of Bidding Documents: wmsu.edu.ph; PhilGeps Website

November 22, 2023

DR. JOSELITO D. MADROÑAL BAC Chairperson for Goods

Section II. Instructions to Bidders

Notes on the Instructions to Bidders

This Section on the Instruction to Bidders (ITB) provides the information necessary for bidders to prepare responsive bids, in accordance with the requirements of the Procuring Entity. It also provides information on bid submission, eligibility check, opening and evaluation of bids, post-qualification, and on the award of contract.

1. Scope of Bid

The Procuring Entity, Western Mindanao State University wishes to receive Bids for the Supply and Delivery of Various Laboratory Supplies, Materials and Equipment of the College of Agriculture for the University (PR-23-10-479).

The Procurement Project (referred to herein as "Project") is composed of *Nineteen (19) items* the details of which are described in Section VII (Technical Specifications).

2. Funding Information

2.1. The GOP through the source of funding as indicated below for *GAA 2023* in the amount of *Three Million Nine Hundred Sixty-Six Thousand pesos (Php 3,966,000.00)*

3. Bidding Requirements

The Bidding for the Project shall be governed by all the provisions of RA No. 9184 and its 2016 revised IRR, including its Generic Procurement Manuals and associated policies, rules and regulations as the primary source thereof, while the herein clauses shall serve as the secondary source thereof.

Any amendments made to the IRR and other GPPB issuances shall be applicable only to the ongoing posting, advertisement, or **IB** by the BAC through the issuance of a supplemental or bid bulletin.

The Bidder, by the act of submitting its Bid, shall be deemed to have verified and accepted the general requirements of this Project, including other factors that may affect the cost, duration and execution or implementation of the contract, project, or work and examine all instructions, forms, terms, and project requirements in the Bidding Documents.

4. Corrupt, Fraudulent, Collusive, and Coercive Practices

The Procuring Entity, as well as the Bidders and Suppliers, shall observe the highest standard of ethics during the procurement and execution of the contract. They or through an agent shall not engage in corrupt, fraudulent, collusive, coercive, and obstructive practices defined under Annex "I" of the 2016 revised IRR of RA No. 9184 or other integrity violations in competing for the Project.

5. Eligible Bidders

- 5.1. Only Bids of Bidders found to be legally, technically, and financially capable will be evaluated.
- 5.3. Pursuant to Section 23.4.1.3 of the 2016 revised IRR of RA No.9184, the Bidder shall have an SLCC that is at least one (1) contract similar to the Project the value of which, adjusted to current prices using the PSA's CPI, must be at least equivalent to:
 - a. For the procurement of Non-expendable Supplies and Services: The Bidder must have completed a single contract that is similar to this Project, equivalent to at least fifty percent (50%) of the ABC.
 - b. For the procurement of Expendable Supplies: The Bidder must have completed a single contract that is similar to this Project, equivalent to at least twenty-five percent (25%) of the ABC.

- c. For procurement where the Procuring Entity has determined, after the conduct of market research, that imposition of either (a) or (b) will likely result to failure of bidding or monopoly that will defeat the purpose of public bidding: the Bidder should comply with the following requirements: [Select either failure or monopoly of bidding based on market research conducted]
 - i. Completed at least two (2) similar contracts, the aggregate amount of which should be equivalent to at least fifty percent (50%) in the case of non-expendable supplies and services or twenty-five percent (25%) in the case of expendable supplies] of the ABC for this Project; and
 - ii. The largest of these similar contracts must be equivalent to at least half of the percentage of the ABC as required above.
- 5.4. The Bidders shall comply with the eligibility criteria under Section 23.4.1 of the 2016 IRR of RA No. 9184.

6. Origin of Goods

There is no restriction on the origin of goods other than those prohibited by a decision of the UN Security Council taken under Chapter VII of the Charter of the UN, subject to Domestic Preference requirements under **ITB** Clause 18.

7. Subcontracts

7.1. The Bidder may subcontract portions of the Project to the extent allowed by the Procuring Entity as stated herein, but in no case more than twenty percent (20%) of the Project.

The Procuring Entity has prescribed that:

- a. Subcontracting is not allowed.
- 7.2. Subcontracting of any portion of the Project does not relieve the Supplier of any liability or obligation under the Contract. The Supplier will be responsible for the acts, defaults, and negligence of any subcontractor, its agents, servants, or workmen as fully as if these were the Supplier's own acts, defaults, or negligence, or those of its agents, servants, or workmen.

8. Pre-Bid Conference

The Procuring Entity will hold a pre-bid conference for this Project November 29, 20239:30 AM at BAC Office, 2nd Floor Admin. Building, Western Mindanao State University, Baliwasan, Zamboanga City as indicated in paragraph 6 of the IB.

9. Clarification and Amendment of Bidding Documents

Prospective bidders may request for clarification on and/or interpretation of any part of the Bidding Documents. Such requests must be in writing and received by the Procuring Entity, either at its given address or through electronic mail indicated in the **IB**, at least ten (10) calendar days before the deadline set for the submission and receipt of Bids.

10. Documents comprising the Bid: Eligibility and Technical Components

- 10.1. The first envelope shall contain the eligibility and technical documents of the Bid as specified in **Section VIII** (Checklist of Technical and Financial **Documents**).
- 10.2. The Bidder's SLCC as indicated in **ITB** Clause5.3 should have been completed within [state relevant period as provided in paragraph 2 of the **IB**] prior to the deadline for the submission and receipt of bids.
- 10.3. If the eligibility requirements or statements, the bids, and all other documents for submission to the BAC are in foreign language other than English, it must be accompanied by a translation in English, which shall be authenticated by the appropriate Philippine foreign service establishment, post, or the equivalent office having jurisdiction over the foreign bidder's affairs in the Philippines. Similar to the required authentication above, for Contracting Parties to the Apostille Convention, only the translated documents shall be authenticated through an apostille pursuant to GPPB Resolution No. 13-2019 dated 23 May 2019. The English translation shall govern, for purposes of interpretation of the bid.

11. Documents comprising the Bid: Financial Component

- 11.1. The second bid envelope shall contain the financial documents for the Bid as specified in Section VIII (Checklist of Technical and Financial Documents).
- 11.2. If the Bidder claims preference as a Domestic Bidder or Domestic Entity, a certification issued by DTI shall be provided by the Bidder in accordance with Section 43.1.3 of the 2016 revised IRR of RA No. 9184.
- 11.3. Any bid exceeding the ABC indicated in paragraph 1 of the **IB** shall not be accepted.
- 11.4. For Foreign-funded Procurement, a ceiling may be applied to bid prices provided the conditions are met under Section 31.2 of the 2016 revised IRR of RA No. 9184.

12. Bid Prices

- 12.1. Prices indicated on the Price Schedule shall be entered separately in the following manner:
 - a. For Goods offered from within the Procuring Entity's country:
 - i. The price of the Goods quoted EXW (ex-works, ex-factory, exwarehouse, ex-showroom, or off-the-shelf, as applicable);
 - ii. The cost of all customs duties and sales and other taxes already paid or payable;
 - iii. The cost of transportation, insurance, and other costs incidental to delivery of the Goods to their final destination; and
 - iv. The price of other (incidental) services, if any, listed in e.
 - b. For Goods offered from abroad:

- i. Unless otherwise stated in the **BDS**, the price of the Goods shall be quoted delivered duty paid (DDP) with the place of destination in the Philippines as specified in the **BDS**. In quoting the price, the Bidder shall be free to use transportation through carriers registered in any eligible country. Similarly, the Bidder may obtain insurance services from any eligible source country.
- ii. The price of other (incidental) services, if any, as listed in **Section VII (Technical Specifications).**
- 12.2. [Include if Framework Agreement will be used:] For Framework Agreement, the following should also apply in addition to Clause 12.1:
 - a. For a single year Framework Agreement, the prices quoted by the Bidder shall be fixed during the Bidder's performance of the contract and not subject to variation or escalation on any account. Price schedules required under Clause 12.1 shall be submitted with the bidding documents.
 - b. For a multi-year Framework Agreement, the prices quoted by the Bidder during submission of eligibility documents shall be the ceiling and the price quoted during mini-competition must not exceed the initial price offer. The price quoted during call for mini-competition shall be fixed during the Bidder's performance of that Call-off and not subject to variation or escalation on any account. Price schedules required under Clause 12.1 shall be submitted with the bidding documents.

13. Bid and Payment Currencies

- 13.1. For Goods that the Bidder will supply from outside the Philippines, the bid prices may be quoted in the local currency or tradeable currency accepted by the BSP at the discretion of the Bidder. However, for purposes of bid evaluation, Bids denominated in foreign currencies, shall be converted to Philippine currency based on the exchange rate as published in the BSP reference rate bulletin on the day of the bid opening.
- 13.2. Payment of the contract price shall be made in:
 - a. Philippine Pesos.

14. Bid Security

14.1. The Bidder shall submit a Bid Securing Declaration² or any form of Bid Security in the amount indicated in the **BDS**, which shall be not less than the percentage of the ABC in accordance with the schedule in the **BDS**.

14.2. The Bid and bid security shall be valid until **120 days**. Any Bid not accompanied by an acceptable bid security shall be rejected by the Procuring Entity as non-responsive.

15. Sealing and Marking of Bids

Each Bidder shall submit one copy of the first and second components of its Bid.

² In the case of Framework Agreement, the undertaking shall refer to entering into contract with the Procuring Entity and furnishing of the performance security or the performance securing declaration within ten (10) calendar days from receipt of Notice to Execute Framework Agreement.

The Procuring Entity may request additional hard copies and/or electronic copies of the Bid. However, failure of the Bidders to comply with the said request shall not be a ground for disqualification.

If the Procuring Entity allows the submission of bids through online submission or any other electronic means, the Bidder shall submit an electronic copy of its Bid, which must be digitally signed. An electronic copy that cannot be opened or is corrupted shall be considered non-responsive and, thus, automatically disqualified.

16. Deadline for Submission of Bids

16.1. The Bidders shall submit on the specified date and time and either at its physical address or through online submission as indicated in paragraph 7 of the **IB.**

17. Opening and Preliminary Examination of Bids

17.1. The BAC shall open the Bids in public at the time, on the date, and at the place specified in paragraph 9 of the **IB**. The Bidders' representatives who are present shall sign a register evidencing their attendance. In case videoconferencing, webcasting or other similar technologies will be used, attendance of participants shall likewise be recorded by the BAC Secretariat.

In case the Bids cannot be opened as scheduled due to justifiable reasons, the rescheduling requirements under Section 29 of the 2016 revised IRR of RA No. 9184 shall prevail.

17.2. The preliminary examination of bids shall be governed by Section 30 of the 2016 revised IRR of RA No. 9184.

18. Domestic Preference

18.1. The Procuring Entity will grant a margin of preference for the purpose of comparison of Bids in accordance with Section 43.1.2 of the 2016 revised IRR of RA No. 9184.

19. Detailed Evaluation and Comparison of Bids

- 19.1. The Procuring BAC shall immediately conduct a detailed evaluation of all Bids rated "passed," using non-discretionary pass/fail criteria. The BAC shall consider the conditions in the evaluation of Bids under Section 32.2 of the 2016 revised IRR of RA No. 9184.
- 19.2. If the Project allows partial bids, bidders may submit a proposal on any of the lots or items, and evaluation will be undertaken on a per lot or item basis, as the case maybe. In this case, the Bid Security as required by **ITB** Clause 15 shall be submitted for each lot or item separately.
- 19.3. The descriptions of the lots or items shall be indicated in **Section VII** (**Technical Specifications**), although the ABCs of these lots or items are indicated in the **BDS** for purposes of the NFCC computation pursuant to Section 23.4.2.6 of the 2016 revised IRR of RA No. 9184. The NFCC must be

sufficient for the total of the ABCs for all the lots or items participated in by the prospective Bidder.

- 19.4. The Project shallbe awarded as follows:
 - One Project having several items, which shall be awarded as separate contracts per item.
- 19.5. Except for bidders submitting a committed Line of Credit from a Universal or Commercial Bank in lieu of its NFCC computation, all Bids must include the NFCC computation pursuant to Section 23.4.1.4 of the 2016 revised IRR of RA No. 9184, which must be sufficient for the total of the ABCs for all the lots or items participated in by the prospective Bidder. For bidders submitting the committed Line of Credit, it must be at least equal to ten percent (10%) of the ABCs for all the lots or items participated in by the prospective Bidder.

20. Post-Qualification

20.2. Within a non-extendible period of five (5) calendar days from receipt by the Bidder of the notice from the BAC that it submitted the Lowest Calculated Bid, the Bidder shall submit its latest income and business tax returns filed and paid through the BIR Electronic Filing and Payment System (eFPS) and other appropriate licenses and permits required by law and stated in the **BDS**.

21. Signing of the Contract

21.1. The documents required in Section 37.2 of the 2016 revised IRR of RA No. 9184 shall form part of the Contract. Additional Contract documents are indicated in the **BDS**.

Section III. Bid Data Sheet

Notes on the Bid Data Sheet

The Bid Data Sheet (BDS) consists of provisions that supplement, amend, or specify in detail, information, or requirements included in the ITB found in Section II, which are specific to each procurement.

This Section is intended to assist the Procuring Entity in providing the specific information in relation to corresponding clauses in the ITB and has to be prepared for each specific procurement.

The Procuring Entity should specify in the BDS information and requirements specific to the circumstances of the Procuring Entity, the processing of the procurement, and the bid evaluation criteria that will apply to the Bids. In preparing the BDS, the following aspects should be checked:

- a. Information that specifies and complements provisions of the ITB must be incorporated.
- b. Amendments and/or supplements, if any, to provisions of the ITB as necessitated by the circumstances of the specific procurement, must also be incorporated.

Bid Data Sheet

Source S	ITB						
a. Supply and Delivery of Various Laboratory Equipment and Supplies b. Completed within reasonable period prior to the deadline for the submission and receipt of bids. 7.1 Not Applicable 12 The price of the Goods shall be quoted DDP [state place of destination] or the applicable International Commercial Terms (INCOTERMS) for this Project. 14.1 The bid security shall be in the form of a Bid Securing Declaration, or any of the following forms and amounts: a. The amount of not less two percent (2%) of ABC if bid security is in cash, cashier's/manager's check, bank draft/guarantee or irrevocable letter of credit; or 19.3 L.) Three (3) unit of ANALYTICAL BALANCE Specifications: Model: BP2003P Capacity: 200g Readability: Img Scale Size: 80mm Stable Time: 1s Read Ability: 2mg Liner: 3mg N.W. 6.8kg External Size: 350*215*340mm Package Size: 480*375*515mm G.W. 8.5kg Work Space Height: 240mm Calibration: External Cal. ABC: Php 285,000.00 2.) One (1) unit of BIOSAFETY CABINET Specifications: External Size: (WxDxH): 700*650*1230mm (without base stand) Internal Size (WxDxH): 600*500*540mm Tetsted Opening: Safety Height 200mm(8") Max Opening: 370mm(15") Inflow Velocity: 0.331/0.025m/s Down Flow Velocity: 0.331/0.025m/s HEPA Filter: Two, 99.995% efficiency at 0.3pm. Filter life indicator Front Window: Motorized. Single Layer toughened glass 5mm. anti UV							
b. Completed within reasonable period prior to the deadline for the submission and receipt of bids. 7.1 Not Applicable 12 The price of the Goods shall be quoted DDP [state place of destination] or the applicable International Commercial Terms (INCOTERMS) for this Project. 14.1 The bid security shall be in the form of a Bid Securing Declaration, or any of the following forms and amounts: a. The amount of not less two percent (2%) of ABC if bid security is in cash, cashier's/manager's check, bank draft/guarantee or irrevocable letter of credit; or 19.3 1.) Three (3) unit of ANALYTICAL BALANCE Specifications: Model: BP2003P Capacity: 200g Readability: Img Scale Size: 80mm Stable Time: 1s Read Ability: 2mg Liner: 3mg N.W.: 6.8kg External Size: 350*215*340mm Package Size: 480*375*515mm G.W.: 8.5kg Work Space Height: 240mm Calibration: External Cal. ABC: Php 285,000.00 2.) One (1) unit of BIOSAFETY CABINET Specifications: External Size: (WxDxH): 700*650*1230mm (without base stand) Internal Size (WxDxH): 600*500*540mm Tetsted Opening: Safety Height 200mm(8") Max Opening: 370mm(15") Inflow Velocity: 0.53/1.025m/s Down Flow Velocity: 0.33/0.025m/s HEPA Filter: Two, 99.995% efficiency at 0.3pm. Filter life indicator Front Window: Motorized. Single Layer toughened glass 5mm. anti UV	5.3	For this purpose, contracts similar to the Project shall be:					
submission and receipt of bids. 7.1 Not Applicable 12 The price of the Goods shall be quoted DDP [state place of destination] or the applicable International Commercial Terms (INCOTERMS) for this Project. 14.1 The bid security shall be in the form of a Bid Securing Declaration, or any of the following forms and amounts: a. The amount of not less two percent (2%) of ABC if bid security is in cash, cashier's/manager's check, bank draft/guarantee or irrevocable letter of credit; or 19.3 1.) Three (3) unit of ANALYTICAL BALANCE Specifications: Model: BP2003P Capacity: 200g Readability: Img Scale Size: 80mm Stable Time: 1s Read Ability: 2mg Liner: 3mg N.W.: 6.8kg External Size: 350*215*340mm Package Size: 480*375*515mm G.W.: 8.5kg Work Space Height: 240mm Calibration: External Cal. ABC: Php 285,000.00 2.) One (1) unit of BIOSAFETY CABINET Specifications: External Size: (WxDxH): 700*650*1230mm (without base stand) Internal Size (WxDxH): 600*500*540mm Tetsted Opening: Safety Height 200mm(8") Max Opening: 370mm(15") Inflow Velocity: 0.33/1.025m/s Down Flow Velocity: 0.33/1.025m/s Down Flow Velocity: 0.33/1.025m/s HEPA Filter: Two, 99.995% efficiency at 0.3pm. Filter life indicator Front Window: Motorized. Single Layer toughened glass 5mm. anti UV		a. Supply and Delivery of Various Laboratory Equipment and Supplies					
7.1 Not Applicable The price of the Goods shall be quoted DDP [state place of destination] or the applicable International Commercial Terms (INCOTERMS) for this Project. 14.1 The bid security shall be in the form of a Bid Securing Declaration, or any of the following forms and amounts: a. The amount of not less two percent (2%) of ABC if bid security is in cash, cashier's/manager's check, bank draft/guarantee or irrevocable letter of credit; or 19.3 1.) Three (3) unit of ANALYTICAL BALANCE Specifications: Model: BP2003P Capacity: 200g Readability: Img Scale Size: 80mm Stable Time: Is Read Ability: 2mg Liner: 3mg N.W.: 6.8kg External Size: 350*215*340mm Package Size: 480*375*515mm G.W.: 8.5kg Work Space Height: 240mm Calibration: External Cal. ABC: Php 285,000.00 2.) One (1) unit of BIOSAFETY CABINET Specifications: External Size: (WxDxH): 700*650*1230mm (without base stand) Internal Size (WxDxH): 600*500*540mm Tetsted Opening: Safety Height 200mm(8") Max Opening: 370mm(15") Inflow Velocity: 0.531.025m/s Down Flow Velocity: 0.531.025m/s Down Flow Velocity: 0.531.025m/s Down Flow Velocity: 0.531.025m/s Down Flow Velocity: 0.537.025m/s Down Flow Velocity: 0.537.025m/s Down Flow Velocity: 0.537.025m/s HEPA Filter: Two, 99.995% efficiency at 0.3pm. Filter life indicator Front Window: Motorized. Single Layer toughened glass Smm. anti UV							
applicable International Commercial Terms (INCOTERMS) for this Project. 14.1 The bid security shall be in the form of a Bid Securing Declaration, or any of the following forms and amounts: a. The amount of not less two percent (2%) of ABC if bid security is in cash, cashier's/manager's check, bank draft/guarantee or irrevocable letter of credit; or 19.3 1.) Three (3) unit of ANALYTICAL BALANCE Specifications: Model: BP2003P Capacity: 200g Readability: Img Scale Size: 80mm Stable Time: 1s Read Ability: 2mg Liner: 3mg N.W.: 6.8kg External Size: 350*215*340mm Package Size: 480*375*515mm G.W.: 8.5kg Work Space Height: 240mm Calibration: External Cal. ABC: Php 285,000.00 2.) One (1) unit of BIOSAFETY CABINET Specifications: External Size: (WxDxH): 700*650*1230mm (without base stand) Internal Size (WxDxH): 500*540mm Tetsted Opening: Safery Height 200mm(8") Max Opening: 370mm(15") Inflow Velocity: 0.53/1.025m/s Down Flow Velocity: 0.53/1.025m/s Down Flow Velocity: 0.53/1.025m/s Down Flow Velocity: 0.53/1.025m/s HEPA Filter: Two, 99.995% efficiency at 0.3pm. Filter life indicator Front Window: Motorized. Single Layer toughened glass 5mm. anti UV	7.1	•					
following forms and amounts: a. The amount of not less two percent (2%) of ABC if bid security is in cash, cashier's/manager's check, bank draft/guarantee or irrevocable letter of credit; or 19.3 1.) Three (3) unit of ANALYTICAL BALANCE Specifications: Model: BP2003P Capacity: 200g Readability: Img Scale Size: 80mm Stable Time: 1s Read Ability: 2mg Liner: 3mg N.W.: 6.8kg External Size: 350*215*340mm Package Size: 480*375*515mm G.W.: 8.5kg Work Space Height: 240mm Calibration: External Cal. ABC: Php 285,000.00 2.) One (1) unit of BIOSAFETY CABINET Specifications: External Size: (WxDxH): 700*650*1230mm (without base stand) Internal Size (WxDxH): 600*500*540mm Tetsted Opening: Safety Height 200mm(8") Max Opening: 370mm(15") Inflow Velocity: 0.53/1.025m/s Down Flow Velocity: 0.33/0.025m/s HEPA Filter: Two, 99.95% efficiency at 0.3pm. Filter life indicator Front Window: Motorized. Single Layer toughened glass 5mm. anti UV	12						
cashier's/manager's check, bank draft/guarantee or irrevocable letter of credit; or 19.3 1.) Three (3) unit of ANALYTICAL BALANCE Specifications: Model: BP2003P Capacity: 200g Readability: Img Scale Size: 80mm Stable Time: 1s Read Ability: 2mg Liner: 3mg N.W.: 6.8kg External Size: 350*215*340mm Package Size: 480*375*515mm G.W.: 8.5kg Work Space Height: 240mm Calibration: External Cal. ABC: Php 285,000.00 2.) One (1) unit of BIOSAFETY CABINET Specifications: External Size: (WxDxH): 700*650*1230mm (without base stand) Internal Size: (WxDxH): 600*500*540mm Tested Opening: Safety Height 200mm(8") Max Opening: 370mm(15") Inflow Velocity: 0.53/1.025m/s Down Flow Velocity: 0.53/1.025m/s HEPA Filter: Two, 99.995% efficiency at 0.3pm. Filter life indicator Front Window: Motorized. Single Layer toughened glass 5mm. anti UV	14.1						
Specifications: Model: BP2003P Capacity: 200g Readability: Img Scale Size: 80mm Stable Time: Is Read Ability: 2mg Liner: 3mg N.W.: 6.8kg External Size: 350*215*340mm Package Size: 480*375*515mm G.W: 8.5kg Work Space Height: 240mm Calibration: External Cal. ABC: Php 285,000.00 2.) One (1) unit of BIOSAFETY CABINET Specifications: External Size: (WxDxH): 700*650*1230mm (without base stand) Internal Size (WxDxH): 600*500*540mm Tetsted Opening: Safety Height 200mm(8") Max Opening: 370mm(15") Inflow Velocity: 0.531/.025m/s Down Flow Velocity: 0.33/0.025m/s HEPA Filter: Two, 99.995% efficiency at 0.3pm. Filter life indicator Front Window: Motorized. Single Layer toughened glass 5mm. anti UV		cashier's/manager's check, bank draft/guarantee or irrevocable letter of					
Specifications: Model: BP2003P Capacity: 200g Readability: Img Scale Size: 80mm Stable Time: Is Read Ability: 2mg Liner: 3mg N.W.: 6.8kg External Size: 350*215*340mm Package Size: 480*375*515mm G.W: 8.5kg Work Space Height: 240mm Calibration: External Cal. ABC: Php 285,000.00 2.) One (1) unit of BIOSAFETY CABINET Specifications: External Size: (WxDxH): 700*650*1230mm (without base stand) Internal Size (WxDxH): 600*500*540mm Tetsted Opening: Safety Height 200mm(8") Max Opening: 370mm(15") Inflow Velocity: 0.531/.025m/s Down Flow Velocity: 0.33/0.025m/s HEPA Filter: Two, 99.995% efficiency at 0.3pm. Filter life indicator Front Window: Motorized. Single Layer toughened glass 5mm. anti UV	10.2	1) Three (2) writ of ANALYTICAL DALANCE					
Model: BP2003P Capacity: 200g Readability: Img Scale Size: 80mm Stable Time: 1s Read Ability: 2mg Liner: 3mg N.W.: 6.8kg External Size: 350*215*340mm Package Size: 480*375*515mm G.W.: 8.5kg Work Space Height: 240mm Calibration: External Cal. ABC: Php 285,000.00 2.) One (1) unit of BIOSAFETY CABINET Specifications: External Size: (WxDxH): 700*650*1230mm (without base stand) Internal Size (WxDxH): 600*500*540mm Tetsted Opening: Safety Height 200mm(8") Max Opening: 370mm(15") Inflow Velocity: 0.53/1.025m/s Down Flow Velocity: 0.33/0.025m/s HEPA Filter: Two, 99.995% efficiency at 0.3pm. Filter life indicator Front Window: Motorized. Single Layer toughened glass 5mm. anti UV	19.3	1.) Inree (3) unit of ANALYTICAL BALANCE					
Capacity: 200g Readability: 1mg Scale Size: 80mm Stable Time: 1s Read Ability: 2mg Liner: 3mg N.W.: 6.8kg External Size: 350*215*340mm Package Size: 480*375*515mm G.W.: 8.5kg Work Space Height: 240mm Calibration: External Cal. ABC: Php 285,000.00 2.) One (1) unit of BIOSAFETY CABINET Specifications: External Size: (WxDxH): 700*650*1230mm (without base stand) Internal Size (WxDxH): 600*500*540mm Tetsted Opening: Safety Height 200mm(8") Max Opening: 370mm(15") Inflow Velocity: 0.53/1.025m/s Down Flow Velocity: 0.53/0.025m/s HEPA Filter: Two, 99.995% efficiency at 0.3pm. Filter life indicator Front Window: Motorized. Single Layer toughened glass 5mm. anti UV		Specifications:					
Readability: Img Scale Size: 80mm Stable Time: 1s Read Ability: 2mg Liner: 3mg N.W.: 6.8kg External Size: 350*215*340mm Package Size: 480*375*515mm G.W.: 8.5kg Work Space Height: 240mm Calibration: External Cal. ABC: Php 285,000.00 2.) One (1) unit of BIOSAFETY CABINET Specifications: External Size: (WxDxH): 700*650*1230mm (without base stand) Internal Size (WxDxH): 600*500*540mm Tetsted Opening: Safety Height 200mm(8") Max Opening: 370mm(15") Inflow Velocity: 0.53/1.025m/s Down Flow Velocity: 0.33/0.025m/s HEPA Filter: Two, 99.995% efficiency at 0.3pm. Filter life indicator Front Window: Motorized. Single Layer toughened glass 5mm. anti UV		Model: BP2003P					
Readability: Img Scale Size: 80mm Stable Time: 1s Read Ability: 2mg Liner: 3mg N.W.: 6.8kg External Size: 350*215*340mm Package Size: 480*375*515mm G.W.: 8.5kg Work Space Height: 240mm Calibration: External Cal. ABC: Php 285,000.00 2.) One (1) unit of BIOSAFETY CABINET Specifications: External Size: (WxDxH): 700*650*1230mm (without base stand) Internal Size (WxDxH): 600*500*540mm Tetsted Opening: Safety Height 200mm(8") Max Opening: 370mm(15") Inflow Velocity: 0.53/1.025m/s Down Flow Velocity: 0.33/0.025m/s HEPA Filter: Two, 99.995% efficiency at 0.3pm. Filter life indicator Front Window: Motorized. Single Layer toughened glass 5mm. anti UV							
Scale Size: 80mm Stable Time: 1s Read Ability: 2mg Liner: 3mg N.W.: 6.8kg External Size: 350*215*340mm Package Size: 480*375*515mm G.W.: 8.5kg Work Space Height: 240mm Calibration: External Cal. ABC: Php 285,000.00 2.) One (1) unit of BIOSAFETY CABINET Specifications: External Size: (WxDxH): 700*650*1230mm (without base stand) Internal Size (WxDxH): 600*500*540mm Tetsted Opening: Safety Height 200mm(8") Max Opening: 370mm(15") Inflow Velocity: 0.53/1.025m/s Down Flow Velocity: 0.33/0.025m/s HEPA Filter: Two, 99.995% efficiency at 0.3pm. Filter life indicator Front Window: Motorized. Single Layer toughened glass 5mm. anti UV							
Read Ability: 2mg Liner: 3mg N.W.: 6.8kg External Size: 350*215*340mm Package Size: 480*375*515mm G.W.: 8.5kg Work Space Height: 240mm Calibration: External Cal. ABC: Php 285,000.00 2.) One (1) unit of BIOSAFETY CABINET Specifications: External Size: (WxDxH): 700*650*1230mm (without base stand) Internal Size (WxDxH): 600*500*540mm Tetsted Opening: Safety Height 200mm(8") Max Opening: 370mm(15") Inflow Velocity: 0.53/1.025m/s Down Flow Velocity: 0.33/0.025m/s HEPA Filter: Two, 99.995% efficiency at 0.3pm. Filter life indicator Front Window: Motorized. Single Layer toughened glass 5mm. anti UV		• •					
Read Ability: 2mg Liner: 3mg N.W.: 6.8kg External Size: 350*215*340mm Package Size: 480*375*515mm G.W.: 8.5kg Work Space Height: 240mm Calibration: External Cal. ABC: Php 285,000.00 2.) One (1) unit of BIOSAFETY CABINET Specifications: External Size: (WxDxH): 700*650*1230mm (without base stand) Internal Size (WxDxH): 600*500*540mm Tetsted Opening: Safety Height 200mm(8") Max Opening: 370mm(15") Inflow Velocity: 0.53/1.025m/s Down Flow Velocity: 0.33/0.025m/s HEPA Filter: Two, 99.995% efficiency at 0.3pm. Filter life indicator Front Window: Motorized. Single Layer toughened glass 5mm. anti UV		Stable Time: 1s					
Liner: 3mg N.W.: 6.8kg External Size: 350*215*340mm Package Size: 480*375*515mm G.W.: 8.5kg Work Space Height: 240mm Calibration: External Cal. ABC: Php 285,000.00 2.) One (1) unit of BIOSAFETY CABINET Specifications: External Size: (WxDxH): 700*650*1230mm (without base stand) Internal Size (WxDxH): 600*500*540mm Tetsted Opening: Safety Height 200mm(8") Max Opening: 370mm(15") Inflow Velocity: 0.53/1.025m/s Down Flow Velocity: 0.33/0.025m/s HEPA Filter: Two, 99.995% efficiency at 0.3pm. Filter life indicator Front Window: Motorized. Single Layer toughened glass 5mm. anti UV							
N.W.: 6.8kg External Size: 350*215*340mm Package Size: 480*375*515mm G.W.: 8.5kg Work Space Height: 240mm Calibration: External Cal. ABC: Php 285,000.00 2.) One (1) unit of BIOSAFETY CABINET Specifications: External Size: (WxDxH): 700*650*1230mm (without base stand) Internal Size (WxDxH): 600*500*540mm Tetsted Opening: Safety Height 200mm(8") Max Opening: 370mm(15") Inflow Velocity: 0.53/1.025m/s Down Flow Velocity: 0.33/0.025m/s HEPA Filter: Two, 99.995% efficiency at 0.3pm. Filter life indicator Front Window: Motorized. Single Layer toughened glass 5mm. anti UV							
External Size: 350*215*340mm Package Size: 480*375*515mm G.W.: 8.5kg Work Space Height: 240mm Calibration: External Cal. ABC: Php 285,000.00 2.) One (1) unit of BIOSAFETY CABINET Specifications: External Size: (WxDxH): 700*650*1230mm (without base stand) Internal Size (WxDxH): 600*500*540mm Tetsted Opening: Safety Height 200mm(8") Max Opening: 370mm(15") Inflow Velocity: 0.53/1.025m/s Down Flow Velocity: 0.33/0.025m/s HEPA Filter: Two, 99.995% efficiency at 0.3pm. Filter life indicator Front Window: Motorized. Single Layer toughened glass 5mm. anti UV		ě					
Package Size: 480*375*515mm G.W.: 8.5kg Work Space Height: 240mm Calibration: External Cal. ABC: Php 285,000.00 2.) One (1) unit of BIOSAFETY CABINET Specifications: External Size: (WxDxH): 700*650*1230mm (without base stand) Internal Size (WxDxH): 600*500*540mm Tetsted Opening: Safety Height 200mm(8") Max Opening: 370mm(15") Inflow Velocity: 0.53/1.025m/s Down Flow Velocity: 0.33/0.025m/s HEPA Filter: Two, 99.995% efficiency at 0.3pm. Filter life indicator Front Window: Motorized. Single Layer toughened glass 5mm. anti UV							
G.W.: 8.5kg Work Space Height: 240mm Calibration: External Cal. ABC: Php 285,000.00 2.) One (1) unit of BIOSAFETY CABINET Specifications: External Size: (WxDxH): 700*650*1230mm (without base stand) Internal Size (WxDxH): 600*500*540mm Tetsted Opening: Safety Height 200mm(8") Max Opening: 370mm(15") Inflow Velocity: 0.53/1.025m/s Down Flow Velocity: 0.33/0.025m/s HEPA Filter: Two, 99.995% efficiency at 0.3pm. Filter life indicator Front Window: Motorized. Single Layer toughened glass 5mm. anti UV							
Work Space Height: 240mm Calibration: External Cal. ABC: Php 285,000.00 2.) One (1) unit of BIOSAFETY CABINET Specifications: External Size: (WxDxH): 700*650*1230mm (without base stand) Internal Size (WxDxH): 600*500*540mm Tetsted Opening: Safety Height 200mm(8") Max Opening: 370mm(15") Inflow Velocity: 0.53/1.025m/s Down Flow Velocity: 0.33/0.025m/s HEPA Filter: Two, 99.995% efficiency at 0.3pm. Filter life indicator Front Window: Motorized. Single Layer toughened glass 5mm. anti UV							
Calibration: External Cal. ABC: Php 285,000.00 2.) One (1) unit of BIOSAFETY CABINET Specifications: External Size: (WxDxH): 700*650*1230mm (without base stand) Internal Size (WxDxH): 600*500*540mm Tetsted Opening: Safety Height 200mm(8") Max Opening: 370mm(15") Inflow Velocity: 0.53/1.025m/s Down Flow Velocity: 0.33/0.025m/s HEPA Filter: Two, 99.995% efficiency at 0.3pm. Filter life indicator Front Window: Motorized. Single Layer toughened glass 5mm. anti UV							
2.) One (1) unit of BIOSAFETY CABINET Specifications: External Size: (WxDxH): 700*650*1230mm (without base stand) Internal Size (WxDxH): 600*500*540mm Tetsted Opening: Safety Height 200mm(8") Max Opening: 370mm(15") Inflow Velocity: 0.53/1.025m/s Down Flow Velocity: 0.33/0.025m/s HEPA Filter: Two, 99.995% efficiency at 0.3pm. Filter life indicator Front Window: Motorized. Single Layer toughened glass 5mm. anti UV		•					
External Size: (WxDxH): 700*650*1230mm (without base stand) Internal Size (WxDxH): 600*500*540mm Tetsted Opening: Safety Height 200mm(8") Max Opening: 370mm(15") Inflow Velocity: 0.53/1.025m/s Down Flow Velocity: 0.33/0.025m/s HEPA Filter: Two, 99.995% efficiency at 0.3pm. Filter life indicator Front Window: Motorized. Single Layer toughened glass 5mm. anti UV		ABC: Php 285,000.00					
External Size: (WxDxH): 700*650*1230mm (without base stand) Internal Size (WxDxH): 600*500*540mm Tetsted Opening: Safety Height 200mm(8") Max Opening: 370mm(15") Inflow Velocity: 0.53/1.025m/s Down Flow Velocity: 0.33/0.025m/s HEPA Filter: Two, 99.995% efficiency at 0.3pm. Filter life indicator Front Window: Motorized. Single Layer toughened glass 5mm. anti UV		2.) One (1) unit of BIOSAFETY CABINET					
Internal Size (WxDxH): 600*500*540mm Tetsted Opening: Safety Height 200mm(8") Max Opening: 370mm(15") Inflow Velocity: 0.53/1.025m/s Down Flow Velocity: 0.33/0.025m/s HEPA Filter: Two, 99.995% efficiency at 0.3pm. Filter life indicator Front Window: Motorized. Single Layer toughened glass 5mm. anti UV		Specifications:					
Tetsted Opening: Safety Height 200mm(8") Max Opening: 370mm(15") Inflow Velocity: 0.53/1.025m/s Down Flow Velocity: 0.33/0.025m/s HEPA Filter: Two, 99.995% efficiency at 0.3pm. Filter life indicator Front Window: Motorized. Single Layer toughened glass 5mm. anti UV							
Max Opening: 370mm(15") Inflow Velocity: 0.53/1.025m/s Down Flow Velocity: 0.33/0.025m/s HEPA Filter: Two, 99.995% efficiency at 0.3pm. Filter life indicator Front Window: Motorized. Single Layer toughened glass 5mm. anti UV		Internal Size (WxDxH): 600*500*540mm					
Inflow Velocity: 0.53/1.025m/s Down Flow Velocity: 0.33/0.025m/s HEPA Filter: Two, 99.995% efficiency at 0.3pm. Filter life indicator Front Window: Motorized. Single Layer toughened glass 5mm. anti UV		Tetsted Opening: Safety Height 200mm(8")					
Down Flow Velocity: 0.33/0.025m/s HEPA Filter: Two, 99.995% efficiency at 0.3pm. Filter life indicator Front Window: Motorized. Single Layer toughened glass 5mm. anti UV		Max Opening: 370mm(15")					
HEPA Filter: Two, 99.995% efficiency at 0.3pm. Filter life indicator Front Window: Motorized. Single Layer toughened glass 5mm. anti UV		Inflow Velocity: 0.53/1.025m/s					
Front Window: Motorized. Single Layer toughened glass 5mm. anti UV		Down Flow Velocity: 0.33/0.025m/s					
		HEPA Filter: Two, 99.995% efficiency at 0.3pm. Filter life indicator					
Noise: 67 dB		Front Window: Motorized. Single Layer toughened glass 5mm. anti UV					
		Noise: 67 dB					

UV Lamp: 15W*1 UV timer, UV life indicator, emission of 253.7 nanometers for

most efficient decontamination

LED Lamp: 8W*2 Illumination: 1000Lux Consumption: 700W

Socket: Two, total load of two sockets: 500W

Display: LCD Display

Control System: Microprocessor

Airflow System: 70% air recirculation, 30% air exhaust

Visual and Audio Alarm: Filter replacement, window over height, abnormal air

flow velocity; High filter pressure alarm

Materials: work zone - 304 stainless steel, main body - cold-rolled steel with anti-

bacteria powder coating

Work Surface Height: 750mm with optional base stand

Power Supply: AC220V/60HZ

Standard Accessory: LED Lamp*2, UV Lamp*1, Remote Control, Waterproof

sockets*2, base stand

Optional Accessory: SS Water tap*1, SS Gas tap*1

Packing Size (without base stand): Carton: 730*787*1450mm

Wood: 860*780*1420mm

Gross Weight (without base stand): Carton: 120kg

wood: 140kg

Packing Size (with base stand): Carton: 730*787*1450mm

Wood: 860*780*1420mm

Gross Weight (with base stand): Carton: 120kg

wood: 140kg

ABC: Php 400,000.00

3.) One (1) unit of COLORIMETER

Key Features

- -Advance from visual to electronic color measurement with confidence
- -Interpret result easily with visual color comparison mode and direct digital reading
- -Obtain quality checks with the on-screen warning system-results displayed in green, yellow and red
- -Easily set time, date, preferences, and projects through the intuitive touch screen
- -Save 20,000 individual readings to the internal memory
- -Internationally recognized industry standards

Includes

- -plastic and glass curvettes
- $\hbox{\it -color reference standards}$
- -cell divider
- -screwdriver
- -USB power supply and cable
- -four AA batteries
- -and hard-sided carrying case

ABC: Php 740,000.00

4.) One (1) unit of CENTRIFUGE

Specifications:

Max Capacity: 6*50ml Max Speed: 4000rpm Max RCF: 2250xg Timing Range: 99min Speed Precision: 2%

Noise: 65dB

Consumption: 150w

Power Supply: AC220V, 50/60Hz

External Size (L*W*H)mm: 450*370*280

Net Weight (kg): 18

Package Size (L*W*H)mm: 470*400*375

Gross Weight(kg): 22 Rotor: Angle Rotor

no. 4M0001 Capacity: 6*50ml

ABC: Php 180,000.00

5.) Two (2) unit of SAFETY CHEMICAL STORAGE SHELF/CABINET

Specifications:

External dimensions (mm): 470x1800x900

Inner dimensions (mm): 440x860x260 (x3 stages); 860x440x382 (x2 stages) Main unit material: 20mm thick particle board (surface: ply plywood

(antibacterial), cosmetic board) with rails/steel

Shelf load tolerance: Fixed shelf/30 kg, rail shelf/20kg

mm Tana: 260, 382 pitch

Drawer: 430mm (slide rail shelf)

Weight: 81kg

Accessories: Drug tray: 9 pieces

Consolidated metal bracket: bolt x 2 pieces Fixed metal bracket: L metal bracket x 2 pieces

ABC: Php 200,000.00

6.) Three (3) unit of BINOCULAR 5 MP DIGITAL MICROSCOPE

Specifications:

- -Binocular model
- -Integrated 5.0 MP CMOS color USB.2 camera
- -2592x1944 pixels
- -7 frames per second (2592x1944 pixels)
- -27 frames per second (1280x960 pixels)
- -Imagefocus Alpha software
- -CAMERA: -digital bScope microscopes
- -5.0 MP 1/2.5 inch CMOS USB-2.0 camera, 24 bits color depth, 7 frames-per second (1280x960 pixels)
- -dynamic range is 76 db and signal/noise ratio 41 db
- -supplied with ImageFocus Alpha Software
- -USB-2.0 cable and a micrometer 1mm/100 calibration slide
- -SOFTWARE: the capture and analysis imagefocus alpha software allows to save images in .jpeg, .tif, .bmp or dicom formats as well as .avi format videos. measurements and annotations can be done on live or captured images. compatible with windows 7, 8 and 10 both 32 and 64 bits configurations. a Mac

OS version is also available. Free updates can be downloaded from our website.

ABC: Php 660,000.00

7.) Two (2) unit of DIGITAL VERNIER CALIPER 150mm STAINLESS STEEL

Specifications:

Type: Digital

Igaging Ez Cal Ip54 0-12" Super Large Lcd Display Digital Caliper Igaging Igaging Ez Cal Ip54 0-12" Super Large Lcd

Display Digital Caliper

ABC: Php 14,000.00

8.) One (1) unit of LABORATORY WATER DISTILLER DISTILLING **APPARATUS**

Specifications:

Voltage: 110-120 volt

Water Flow Rate: 1 litre/minute or higher Water Pressure: Minimum Pressure 3 p.s.i Distillate Temperature: 25-35 Degree C

Conductivity: 3.0 - 4.0 S per cm

Water Still Output: 4 liters/hour or higher

PH: 5.0 - 6.5.

ABC: Php 70,000.00

9.) One (1) unit of FUMEHOOD

Specifications:

External Size (W*D*H): 1000*800*2515mm Instrument Size (W*D*H): 790*600*870mm

Work Surface Height: 900mm

Max Opening: 750mm Air Velocity: 0.3~0.8m/s

System Exhaust Volume: 570m3/h

Power Supply: 220V/60Hz Switches: Fan & Light Sash: Safety Glass

Superstructure: Epoxy powder coated Steel Inner Liner: Acid & Alkali resistant fiber glass

Base Cabinet: Safety storage cabinet or normal base cabinet Water outlet & cupsink: Polypropylene or epoxy resin cupsink

Work top: Chemical resistant worktop Color coded for gas and water valve

Remote control

With complete accessories and Installation

With On Site Training

ABC: Php 310,000.00

10.) Five (5) unit of HOTPLATE with MAGNETIC STIRRER Specifications:

Work plate Dimension (W x D): 184 x 184mm

(7 inch)

Work Plate Material: White Glass Ceramic

Motor Type: Brushless DC Motor

Stirring Position: 1

Max. Stirring Quantity: 20L

Max. Magnetic Bar (Length): 80mm

Speed Range: 100~2000rpm, Resolution±1rpm

Speed Display: LCD Temp. Display: LCD

Heating Temp. Range: Room Temp. -5000C, Increment 10C Temp. Control |Accuracy: ±10C (<1000C) ±1% (>1000C)

Max. Heating plate Temp.: up to 5500C

Overheating Protection: 5800C Temp. Display Accuracy: ±10C

External Temp. Sensor: PT1000 (Accuracy ±0.20C)

"HOT" warning at 50 degrees C

ABC: Php 225,000.00

11.) Three (3) unit of BENCH TOP pH METER

Specifications:

PH Range: 0.00~14.00ph PH Accuracy: 0.05ph Resolution: 0.01ph

Calibration Points: 2 points

Calibration solutions: (ph4.01/7.00/10.01)

mV Range: -1999~1999mV mV Accuracy: 10mV Resolution: 1mV

Temperature Compensation: 0~100 celcius, manual

Connector: BNC, 3.5mm jack socket

Display: LCD

Power Requirements: DC9V/400mA power adapter

Dimensions(mm): at least 210*205*65

ABC: Php 240,000.00

12.) Two (2) unit of SOIL MOISTURE TESTER/METER

Specifications: Sensor Type: PIN

Content Analyzer/Range: 0~80%

Digital Display: LCD

Restore: 99 groups of measurements Accuracy: \pm (0.5% n+1) or higher

Resolution: 0.1

Condition Temp.: 0~500C Humidity: <90% RH Power Supply: 4 x 1.5 V

Statistical Available: LastValue/MeanValue/Max Value, Min Value/Number of

Readings

ABC: Php 20,000.00

13.) One (1) unit of ADJUSTABLE VOLUME PIPETTOR (10-100µl)

Specifications:

Chemical resistant PTFE O-rings and seals that can handle solvents

PDF nozzle and PP shaft

Fully autoclavable

UV resistant for flexible sterilization

One touch calibration

Wetted materials are made up of at least stainless steel (SS) and polypropylene

(PP) plunger assembly Volume of 10-100μL

Increments of 0.1 µL

Accuracy of $\pm 2.0\%$ to $\pm 0.8\%$

Tip ejector is present

Comes with pipette tips (1000pcs/pack)

ABC: Php 50,000.00

14.) Four (4) unit of SOIL PARAMETER SENSOR SET

Compose of the ff. sensors:

Soil Nitrogen Concentration Sensor

Soil Phosphorus Concentration Sensor

Soil Potassium Concentration Sensor

Range: 1-999mg/kg

±2% F.S..

ABC: Php 60,000.00

15.) One (1) unit of SPECTROPHOTOMETER

Specifications:

Optical System: Single beam, grating 1200lines/mm

Wavelength range: 200-1020mm

Spectral bandwith: 4nm Wavelength accuracy: 1.8nm Wavelength repeatability: 0.5nm

Photometric Accuracy: 0.002A(0-0.5Abs), 0.004A (0.5-1.0Abs), 0.5%T (0-

100%T)

Photometric repeatability: 0.001Abs(0-0.5Abs), 0.002Abs (0.5-1Abs), 0.2%T (0-

100%T)

Stray light: 0.2%T @ 360nm; 220nm (UV)

Stability: 0.002A/h@500nm

Noise: 0.001A

Display: 128*64 Dots LCD Photometric Mode: T, A, C, E

Photometric range: 0-200%T,-0.301~3.0A

Detector: Silicon Photodiode

Light Source: Deuterium lamp, tungsten lampInput: Membrane keypad

Output: Parallel Print, USB 1.0

Standard Accessories: 1cm glass cuvette *4 units 1cm quartz cuvette *2 1cm

quadruple cuvette holder *1

Optional Accessories: General application software, 1cm standard single lot cuvette holder, long optical path cuvette holder, cuvette, micro cuvette, test tube type absorber rack, solid sample holder, deuterium lamp, tungsten lamp, quadruple cuvette holder, printer, four slot water bath type constant temperature absorption pool, X-Y adjustable micro absorption pool, single bath type constant temperature absorption pool

. Power Supply: AC110V/220 10%, 60/50Hz

- With On Site Training

ABC: Php 250,000.00

16.) Four (4) unit of LABORATORY STAINLESS CART

Specifications:

Material: Solid Stainless Steel Capacity: At least 700lbs

Dimension: 24"W x 26"L x 36"H

Layers:3 With Handle

ABC: Php 60,000.00

17.) Two (2) unit of UV STERILIZATION CABINET

Specifications: Type: with Ozone

UV Ray Wavelength: 253.7/184.9nm

Sterilization Way: 2 sides of UV ray+1 side of Ozone

Capacity: 200L Power: 120W

UV Lamp Materials: Quartz glass Shelves: Standard 2pc. can be optional Internal Size: at least 518x523x778mm External Size: at least 750x663x1200mm

ABC: Php 110,000.00

18.) Two (2) unit of DIGITAL WEIGHING SCALE

Specifications:

Weighing capacity: 15kg or higher

Scale type: Bench Resolution: 87.5

Plug Type: type C-European Plug

Weigh pan Length: 285mm Weigh pan Width: 255mm Weigh pan Height: 90mm Net Weight: 3.75kg or higher

Min. Operating Temp.: +10 degree celcius Min. Operating Temp.: +35 degree celcius.

ABC: Php 60,000.00

19.) Four (4) unit of PORTABLE TEMPERATURE AND HUMIDITY DATA

LOGGER
Specifications:

Temp. Range: -40 degree celcius~85 degree celcius

Humidity Range: 0~100%RH Temperature Accuracy: 0.5 Humidity Accuracy: 3%RH Temperature Resolution: 0.1oC Humidity Resolution: 3%RH

Recording capacity: 16000 points (MAX).

ABC: Php 32,000.00

20.2	All licenses and permits relevant to the Project and the corresponding law requiring it.
21.2	All additional contract documents relevant to the Project that may be required by existing laws and/or the Procuring Entity.

Section IV. General Conditions of Contract

Notes on the General Conditions of Contract

The General Conditions of Contract (GCC) in this Section, read in conjunction with the Special Conditions of Contract in Section V and other documents listed therein, should be a complete document expressing all the rights and obligations of the parties.

Matters governing performance of the Supplier, payments under the contract, or matters affecting the risks, rights, and obligations of the parties under the contract are included in the GCC and Special Conditions of Contract.

Any complementary information, which may be needed, shall be introduced only through the Special Conditions of Contract.

1. Scope of Contract

This Contract shall include all such items, although not specifically mentioned, that can be reasonably inferred as being required for its completion as if such items were expressly mentioned herein. All the provisions of RA No. 9184 and its 2016 revised IRR, including the Generic Procurement Manual, and associated issuances, constitute the primary source for the terms and conditions of the Contract, and thus, applicable in contract implementation. Herein clauses shall serve as the secondary source for the terms and conditions of the Contract.

This is without prejudice to Sections 74.1 and 74.2 of the 2016 revised IRR of RA No. 9184 allowing the GPPB to amend the IRR, which shall be applied to all procurement activities, the advertisement, posting, or invitation of which were issued after the effectivity of the said amendment.

Additional requirements for the completion of this Contract shall be provided in the **Special Conditions of Contract (SCC).**

2. Advance Payment and Terms of Payment

- 2.1. Advance payment of the contract amount is provided under Annex "D" of the revised 2016 IRR of RA No. 9184.
- 2.2. The Procuring Entity is allowed to determine the terms of payment on the partial or staggered delivery of the Goods procured, provided such partial payment shall correspond to the value of the goods delivered and accepted in accordance with prevailing accounting and auditing rules and regulations. The terms of payment are indicated in the **SCC**.

[Include the following clauses if Framework Agreement will be used:]

- 2.3. For a single-year Framework Agreement, prices charged by the Supplier for Goods delivered and/or services performed under a Call-Off shall not vary from the prices quoted by the Supplier in its bid.
- 2.4. For multi-year Framework Agreement, prices charged by the Supplier for Goods delivered and/or services performed under a Call-Off shall not vary from the prices quoted by the Supplier during conduct of Mini-Competition.

3. Performance Security

Within ten (10) calendar days from receipt of the Notice of Award by the Bidder from the Procuring Entity but in no case later than prior to the signing of the Contract by both parties, the successful Bidder shall furnish the performance security in any of the forms prescribed in Section 39 of the 2016 revised IRR of RA No. 9184. [Include if Framework Agreement will be used:] In the case of Framework Agreement, the Bidder may opt to furnish the performance security or a Performance Securing Declaration as defined under the Guidelines on the Use of Framework Agreement.}

4. Inspection and Tests

The Procuring Entity or its representative shall have the right to inspect and/or to test the Goods to confirm their conformity to the Project {[Include if Framework Agreement will be used:]or Framework Agreement} specifications at no extra cost to the Procuring Entity in accordance with the Generic Procurement Manual. In addition to tests in the SCC, Section IV (Technical Specifications) shall specify what inspections and/or tests the Procuring Entity requires, and where they are to be

conducted. The Procuring Entity shall notify the Supplier in writing, in a timely manner, of the identity of any representatives retained for these purposes.

All reasonable facilities and assistance for the inspection and testing of Goods, including access to drawings and production data, shall be provided by the Supplier to the authorized inspectors at no charge to the Procuring Entity.

5. Warranty

- 6.1. In order to assure that manufacturing defects shall be corrected by the Supplier, a warranty shall be required from the Supplier as provided under Section 62.1 of the 2016 revised IRR of RA No. 9184.
- 6.2. The Procuring Entity shall promptly notify the Supplier in writing of any claims arising under this warranty. Upon receipt of such notice, the Supplier shall, repair or replace the defective Goods or parts thereof without cost to the Procuring Entity, pursuant to the Generic Procurement Manual.

6. Liability of the Supplier

The Supplier's liability under this Contract shall be as provided by the laws of the Republic of the Philippines.

If the Supplier is a joint venture, all partners to the joint venture shall be jointly and severally liable to the Procuring Entity.

Section V. Special Conditions of Contract

Notes on the Special Conditions of Contract

Similar to the BDS, the clauses in this Section are intended to assist the Procuring Entity in providing contract-specific information in relation to corresponding clauses in the GCC found in Section IV.

The Special Conditions of Contract (SCC) complement the GCC, specifying contractual requirements linked to the special circumstances of the Procuring Entity, the Procuring Entity's country, the sector, and the Goods purchased. In preparing this Section, the following aspects should be checked:

- a. Information that complements provisions of the GCC must be incorporated.
- b. Amendments and/or supplements to provisions of the GCC as necessitated by the circumstances of the specific purchase, must also be incorporated.

However, no special condition which defeats or negates the general intent and purpose of the provisions of the GCC should be incorporated herein.

Special Conditions of Contract

GCC	Special Conditions of Contract
Clause	
1	[List here any additional requirements for the completion of this Contract. The following requirements and the corresponding provisions may be deleted, amended, or retained depending on its applicability to this Contract:]
	Delivery and Documents –
	For purposes of the Contract, "EXW," "FOB," "FCA," "CIF," "CIP," "DDP" and other trade terms used to describe the obligations of the parties shall have the meanings assigned to them by the current edition of INCOTERMS published by the International Chamber of Commerce, Paris. The Delivery terms of this Contract shall be as follows:
	[For Goods supplied from abroad, state:] "The delivery terms applicable to the Contract are DDP delivered [indicate place of destination]. In accordance with INCOTERMS."
	[For Goods supplied from within the Philippines, state:] "The delivery terms applicable to this Contract are delivered [indicate place of destination]. Risk and title will pass from the Supplier to the Procuring Entity upon receipt and final acceptance of the Goods at their final destination."
	Delivery of the Goods shall be made by the Supplier in accordance with the terms specified in Section VI (Schedule of Requirements).
	For purposes of this Clause the Procuring Entity's Representative at the Project Site is <i>Mr. Alfredo D. Montero</i> , <i>University Supply Officer</i>
	Incidental Services –
	The Supplier is required to provide all of the following services, including additional services, if any, specified in Section VI. Schedule of Requirements:
	a. performance or supervision of on-site assembly and/or start-up of the supplied Goods;b. furnishing of tools required for assembly and/or maintenance of the
	supplied Goods; c. furnishing of a detailed operations and maintenance manual for each appropriate unit of the supplied Goods;
	d. performance or supervision or maintenance and/or repair of the supplied Goods, for a period of time agreed by the parties, provided that this service shall not relieve the Supplier of any warranty obligations under this Contract; and
	e. training of the Procuring Entity's personnel, at the Supplier's plant and/or on-site, in assembly, start-up, operation, maintenance, and/or repair of the supplied Goods.
	The Contract price for the Goods shall include the prices charged by the Supplier for incidental services and shall not exceed the prevailing rates charged to other parties by the Supplier for similar services.

Spare Parts -

The Supplier is required to provide all of the following materials, notifications, and information pertaining to spare parts manufactured or distributed by the Supplier:

Select appropriate requirements and delete the rest.

- a. such spare parts as the Procuring Entity may elect to purchase from the Supplier, provided that this election shall not relieve the Supplier of any warranty obligations under this Contract; and
- b. in the event of termination of production of the spare parts:
 - i. advance notification to the Procuring Entity of the pending termination, in sufficient time to permit the Procuring Entity to procure needed requirements; and
 - ii. following such termination, furnishing at no cost to the Procuring Entity, the blueprints, drawings, and specifications of the spare parts, if requested.

The spare parts and other components required are listed in **Section VI** (**Schedule of Requirements**) and the cost thereof are included in the contract price.

The Supplier shall carry sufficient inventories to assure ex-stock supply of consumable spare parts or components for the Goods for a period of [indicate here the time period specified. If not used indicate a time period of three times the warranty period].

Spare parts or components shall be supplied as promptly as possible, but in any case, within [insert appropriate time period] months of placing the order.

Packaging -

The Supplier shall provide such packaging of the Goods as is required to prevent their damage or deterioration during transit to their final destination, as indicated in this Contract. The packaging shall be sufficient to withstand, without limitation, rough handling during transit and exposure to extreme temperatures, salt and precipitation during transit, and open storage. Packaging case size and weights shall take into consideration, where appropriate, the remoteness of the Goods' final destination and the absence of heavy handling facilities at all points in transit.

The packaging, marking, and documentation within and outside the packages shall comply strictly with such special requirements as shall be expressly provided for in the Contract, including additional requirements, if any, specified below, and in any subsequent instructions ordered by the Procuring Entity.

The outer packaging must be clearly marked on at least four (4) sides as follows:

Name of the Procuring Entity Name of the Supplier Contract Description

	Final Destination Gross weight
	Any special lifting instructions Any special handling instructions Any relevant HAZCHEM classifications
	A packaging list identifying the contents and quantities of the package is to be placed on an accessible point of the outer packaging if practical. If not practical the packaging list is to be placed inside the outer packaging but outside the secondary packaging.
	Transportation –
	Where the Supplier is required under Contract to deliver the Goods CIF, CIP, or DDP, transport of the Goods to the port of destination or such other named place of destination in the Philippines, as shall be specified in this Contract, shall be arranged and paid for by the Supplier, and the cost thereof shall be included in the Contract Price.
	Where the Supplier is required under this Contract to transport the Goods to a specified place of destination within the Philippines, defined as the Project Site, transport to such place of destination in the Philippines, including insurance and storage, as shall be specified in this Contract, shall be arranged by the Supplier, and related costs shall be included in the contract price.
	Where the Supplier is required under Contract to deliver the Goods CIF, CIP or DDP, goods are to be transported on carriers of Philippine registry. In the event that no carrier of Philippine registry is available, goods may be shipped by a carrier which is not of Philippine registry provided that the Supplier obtains and presents to the Procuring Entity certification to this effect from the nearest Philippine consulate to the port of dispatch. In the event that carriers of Philippine registry are available but their schedule delays the Supplier in its performance of this Contract the period from when the Goods were first ready for shipment and the actual date of shipment the period of delay will be considered force majeure.
	The Procuring Entity accepts no liability for the damage of Goods during transit other than those prescribed by INCOTERMS for DDP deliveries. In the case of Goods supplied from within the Philippines or supplied by domestic Suppliers risk and title will not be deemed to have passed to the Procuring Entity until their receipt and final acceptance at the final destination.
	Intellectual Property Rights –
	The Supplier shall indemnify the Procuring Entity against all third-party claims of infringement of patent, trademark, or industrial design rights arising from use of the Goods or any part thereof.
2.2	Not Applicable.
4	The inspections and tests that will be conducted are: all the applicable inspections and tests.

Section VI. Schedule of Requirements

The delivery schedule expressed as weeks/months stipulates hereafter a delivery date which is the date of delivery to the project site.

Item	Description	Quantity	Total	Delivered,
Number	-	,	Total	Weeks/Months
1	ANALYTICAL BALANCE	Three (3)		
	Specifications:			
	specifications.			
	Model: BP2003P			
	Capacity: 200g			
	Readability: 1mg			
	Scale Size: 80mm			
	Stable Time: 1s			
	Read Ability: 2mg			
	Liner: 3mg			
	N.W.: 6.8kg			
	External Size:			
	350*215*340mm			
	Package Size: 480*375*515mm			
	G.W.: 8.5kg			
	Work Space Height: 240mm			
	Calibration: External Cal.			
	Cunoration. External cun			
2	BIOSAFETY CABINET	One (1)		
	Specifications:			
	External Size: (WxDxH):			
	700*650*1230mm (without			
	base stand)			
	Internal Size (WxDxH):			
	600*500*540mm			
	Tetsted Opening: Safety			
	Height 200mm(8")			
	Max Opening: 370mm(15")			
	Inflow Velocity:			
	0.53/1.025m/s			
	Down Flow Velocity:			
	0.33/0.025m/s			
	HEPA Filter: Two, 99.995%			
	efficiency at 0.3pm. Filter life indicator			
	Front Window: Motorized.			
	Single Layer toughened glass			
	5mm. anti UV			
	Noise: 67 dB			
	UV Lamp: 15W*1 UV timer,			
	UV life indicator, emission of			
	253.7 nanometers for most			
	efficient decontamination			
	LED Lamp: 8W*2			
	Illumination: 1000Lux			

	Consumption: 700W Socket: Two, total load of two sockets: 500W Display: LCD Display Control System: Microprocessor Airflow System: 70% air recirculation, 30% air exhaust Visual and Audio Alarm: Filter replacement, window over height, abnormal air flow velocity; High filter pressure alarm		
	Materials: work zone - 304 stainless steel, main body - cold-rolled steel with anti-bacteria powder coating Work Surface Height: 750mm with optional base stand Power Supply:		
	AC220V/60HZ Standard Accessory: LED Lamp*2, UV Lamp*1, Remote Control, Waterproof sockets*2, base stand		
	Optional Accessory: SS Water tap*1, SS Gas tap*1 Packing Size (without base stand): Carton: 730*787*1450mm Wood: 860*780*1420mm Gross Weight (without base		
	stand): Carton: 120kg wood: 140kg Packing Size (with base stand): Carton: 730*787*1450mm Wood: 860*780*1420mm		
	Gross Weight (with base stand): Carton: 120kg wood: 140kg		
3	COLORIMETER	One (1)	
	Key Features		
	-Advance from visual to electronic color measurement with confidence -Interpret result easily with visual color comparison mode and direct digital reading -Obtain quality checks with the on-screen warning system- results displayed in green, yellow and red -Easily set time, date,		

	preferences, and projects through the intuitive touch screen -Save 20,000 individual readings to the internal memory -Internationally recognized industry standards Includes -plastic and glass curvettes -color reference standards -cell divider -screwdriver -USB power supply and cable -four AA batteries -and hard-sided carrying case		
4	CENTRIFUGE Specifications: Max Capacity: 6*50ml Max Speed: 4000rpm Max RCF: 2250xg Timing Range: 99min Speed Precision: 2% Noise: 65dB Consumption: 150w Power Supply: AC220V, 50/60Hz External Size (L*W*H)mm: 450*370*280 Net Weight (kg): 18 Package Size (L*W*H)mm: 470*400*375 Gross Weight(kg): 22 Rotor: Angle Rotor no. 4M0001 Capacity: 6*50ml	One (1)	
5	SAFETY CHEMICAL STORAGE SHELF/CABINET Specifications: External dimensions (mm): 470x1800x900 Inner dimensions (mm): 440x860x260 (x3 stages); 860x440x382 (x2 stages) Main unit material: 20mm thick particle board (surface: ply plywood	Two (2)	

	(antibacterial),cosmetic board)			
	with rails/steel			
	Shelf load tolerance: Fixed			
	shelf/30 kg, rail shelf/20kg			
	mm Tana: 260, 382 pitch			
	_			
	Drawer: 430mm (slide rail			
	shelf)			
	Weight: 81kg			
	Accessories: Drug tray: 9			
	pieces			
	Consolidated metal bracket:			
	bolt x 2 pieces			
	Fixed metal bracket: L metal			
	bracket x 2 pieces			
	1			
6	BINOCULAR 5 MP	Three (3)		
	DIGITAL MICROSCOPE	,		
	Specifications:			
	Specifications.			
	-Binocular model			
	-Integrated 5.0 MP CMOS			
	color USB.2 camera			
	-2592x1944 pixels			
	-7 frames per second			
	(2592x1944 pixels)			
	-27 frames per second			
	(1280x960 pixels)			
	-Imagefocus Alpha software			
	-CAMERA: -digital bScope			
	microscopes			
	-5.0 MP 1/2.5 inch CMOS			
	USB-2.0 camera, 24 bits color			
	depth, 7 frames-per second			
	(1280x960 pixels)			
	-dynamic range is 76 db and			
	signal/noise ratio 41 db			
	-supplied with ImageFocus			
	Alpha Software			
	-USB-2.0 cable and a			
	micrometer 1mm/100			
	calibration slide			
	-SOFTWARE: the capture and			
	analysis imagefocus alpha			
	software allows to save			
	images in .jpeg, .tif, .bmp or			
	dicom formats as well as .avi			
	format videos. measurements			
	and annotations can be done			
	on live or captured images.			
	compatible with windows 7, 8			
	and 10 both 32 and 64 bits			
	configurations. a Mac OS			
	version is also available. Free			
	updates can be downloaded			
	from our website.			
	nomour website.			
			1	

7	DIGITAL VERNIER CALIPER 150mm STAINLESS STEEL Specifications: Type: Digital Igaging Ez Cal Ip54 0-12" Super Large Lcd Display Digital Caliper Igaging Igaging Ez Cal Ip54 0-12" Super Large Lcd Display Digital Caliper	Two (2) unit
8	LABORATORY WATER DISTILLER Specifications: Voltage: 110-120 volt Water Flow Rate: 1 litre/minute or higher Water Pressure: Minimum Pressure 3 p.s.i Distillate Temperature: 25-35 Degree C Conductivity: 3.0 - 4.0 S per cm Water Still Output: 4 liters/hour or higher PH: 5.0 - 6.5.	One (1)
9	FUMEHOOD Specifications: External Size (W*D*H): 1000*800*2515mm Instrument Size (W*D*H): 790*600*870mm Work Surface Height: 900mm Max Opening: 750mm Air Velocity: 0.3~0.8m/s System Exhaust Volume: 570m3/h Power Supply: 220V/60Hz Switches: Fan & Light Sash: Safety Glass Superstructure: Epoxy powder coated Steel Inner Liner: Acid & Alkali resistant fiber glass Base Cabinet: Safety storage cabinet or normal base cabinet Water outlet & cupsink:	One (1)

	Polypropylene or epoxy resin cupsink Work top: Chemical resistant worktop Color coded for gas and water valve Remote control With complete accessories and Installation With On Site Training		
10	HOTPLATE with MAGNETIC STIRRER Specifications: Work plate Dimension (W x D): 184 x 184mm (7 inch) Work Plate Material: White Glass Ceramic Motor Type: Brushless DC Motor Stirring Position: 1 Max. Stirring Quantity: 20L Max. Magnetic Bar (Length): 80mm Speed Range: 100~2000rpm, Resolution±1rpm Speed Display: LCD Temp. Display: LCD Heating Temp. Range: Room Temp5000C, Increment 10C Temp. Control Accuracy: ±10C (<1000C) ±1% (>1000C) Max. Heating plate Temp.: up to 5500C Overheating Protection: 5800C Temp. Display Accuracy: ±10C External Temp. Sensor: PT1000 (Accuracy ±0.20C) "HOT" warning at 50 degrees C	Five (5)	
11	BENCH TOP pH METER Specifications: PH Range: 0.00~14.00ph PH Accuracy: 0.05ph Resolution: 0.01ph Calibration Points: 2 points Calibration solutions: (ph4.01/7.00/10.01) mV Range: -1999~1999mV mV Accuracy: 10mV Resolution: 1mV Temperature Compensation:	Three (3)	

	0~100 celcius, manual Connector: BNC, 3.5mm jack socket Display: LCD Power Requirements: DC9V/400mA power adapter Dimensions(mm): at least 210*205*65			
12	SOIL MOISTURE TESTER/METER Specifications: Sensor Type: PIN Content Analyzer/Range: 0~80% Digital Display: LCD Restore: 99 groups of measurements Accuracy: ± (0.5% n+1) or higher Resolution: 0.1 Condition Temp.: 0~500C Humidity: <90% RH Power Supply: 4 x 1.5 V Statistical Available: LastValue/MeanValue/Max Value, Min Value/Number of Readings	Two unit	(2)	
13	ADJUSTABLE VOLUME PIPETTOR (10-100µl) Specifications: Chemical resistant PTFE Orings and seals that can handle solvents PDF nozzle and PP shaft Fully autoclavable UV resistant for flexible sterilization One touch calibration Wetted materials are made up of at least stainless steel (SS) and polypropylene (PP) plunger assembly Volume of 10-100µL Increments of 0.1µL Accuracy of ±2.0% to ±0.8% Tip ejector is present Comes with pipette tips (1000pcs/pack)	One unit	(1)	
14	SOIL PARAMETER SENSOR SET Compose of the ff. sensors: Soil Nitrogen Concentration Sensor Soil Phosphorus	Four unit	(4)	

	Concentration Sensor Soil Potassium Concentration Sensor Range: 1-999mg/kg ±2% F.S			
15	SPECTROPHOTOMETER Specifications: Optical System: Single beam, grating 1200lines/mm Wavelength range: 200- 1020mm Spectral bandwith: 4nm Wavelength accuracy: 1.8nm Wavelength repeatability: 0.5nm Photometric Accuracy: 0.002A(0-0.5Abs), 0.004A (0.5-1.0Abs), 0.5%T (0- 100%T) Photometric repeatability: 0.001Abs(0-0.5Abs), 0.002Abs (0.5-1Abs), 0.2%T (0-100%T) Stray light: 0.2%T @ 360nm; 220nm (UV) Stability: 0.002A/h@500nm Noise: 0.001A Display: 128*64 Dots LCD Photometric Mode: T, A, C, E Photometric range: 0-200%T,- 0.301~3.0A Detector: Silicon Photodiode Light Source: Deuterium lamp, tungsten lampInput: Membrane keypad Output: Parallel Print, USB 1.0 Standard Accessories: 1cm glass cuvette *4 units 1cm quartz cuvette *2 1cm quadruple cuvette holder *1 Optional Accessories: General application software, 1cm standard single lot cuvette holder, long optical path cuvette holder, cuvette, micro cuvette, test tube type absorber rack, solid sample holder, deuterium lamp, tungsten lamp, quadruple cuvette holder, printer, four slot water bath type constant temperature absorption pool, X-Y adjustable micro absorption pool, single bath	One unit	(1)	
	type constant temperature			

			1	<u> </u>
	absorption pool . Power Supply: AC110V/220 10%, 60/50Hz - With On Site Training			
16	LABORATORY STAINLESS CART Specifications: Material: Solid Stainless Steel Capacity: At least 700lbs Dimension: 24"W x 26"L x 36"H Layers:3 With Handle	Four (4)		
17	UV STERILIZATION CABINET Specifications: Type: with Ozone UV Ray Wavelength: 253.7/184.9nm Sterilization Way: 2 sides of UV ray+1 side of Ozone Capacity: 200L Power: 120W UV Lamp Materials: Quartz glass Shelves: Standard 2pc. can be optional Internal Size: at least 518x523x778mm External Size: at least 750x663x1200mm	Two (2) unit		
18	DIGITAL WEIGHING SCALE Specifications: Weighing capacity: 15kg or higher Scale type: Bench Resolution: 87.5 Plug Type: type C-European Plug Weigh pan Length: 285mm Weigh pan Width: 255mm Weigh pan Height: 90mm Net Weight: 3.75kg or higher Min. Operating Temp.: +10 degree celcius Min. Operating Temp.: +35 degree celcius.	Two (2) unit		
19	PORTABLE TEMPERATURE AND HUMIDITY DATA LOGGER	Four (4) unit		

Sp	ecifications:		
Te	emp. Range: -40 degree		
cel	lcius~85 degree celcius		
Hu	midity Range: 0~100%RH		
Te	emperature Accuracy: 0.5		
Hu	midity Accuracy: 3%RH		
Te	emperature Resolution:		
0.1	loC		
Hu	imidity Resolution: 3%RH		
Re	ecording capacity: 16000		
po	ints(MAX).		

Section VII. Technical Specifications

Notes for Preparing the Technical Specifications

A set of precise and clear specifications is a prerequisite for Bidders to respond realistically and competitively to the requirements of the Procuring Entity without qualifying their Bids. In the context of Competitive Bidding, the specifications (*e.g.* production/delivery schedule, manpower requirements, and after-sales service/parts, descriptions of the lots or items) must be prepared to permit the widest possible competition and, at the same time, present a clear statement of the required standards of workmanship, materials, and performance of the goods and services to be procured. Only if this is done will the objectives of transparency, equity, efficiency, fairness, and economy in procurement be realized, responsiveness of bids be ensured, and the subsequent task of bid evaluation and post-qualification facilitated. The specifications should require that all items, materials and accessories to be included or incorporated in the goods be new, unused, and of the most recent or current models, and that they include or incorporate all recent improvements in design and materials unless otherwise provided in the Contract.

Samples of specifications from previous similar procurements are useful in this respect. The use of metric units is encouraged. Depending on the complexity of the goods and the repetitiveness of the type of procurement, it may be advantageous to standardize the General Technical Specifications and incorporate them in a separate subsection. The General Technical Specifications should cover all classes of workmanship, materials, and equipment commonly involved in manufacturing similar goods. Deletions or addenda should then adapt the General Technical Specifications to the particular procurement.

Care must be taken in drafting specifications to ensure that they are not restrictive. In the specification of standards for equipment, materials, and workmanship, recognized Philippine and international standards should be used as much as possible. Where other particular standards are used, whether national standards or other standards, the specifications should state that equipment, materials, and workmanship that meet other authoritative standards, and which ensure at least a substantially equal quality than the standards mentioned, will also be acceptable. The following clause may be inserted in the Special Conditions of Contract or the Technical Specifications.

Sample Clause: Equivalency of Standards and Codes

Wherever reference is made in the Technical Specifications to specific standards and codes to be met by the goods and materials to be furnished or tested, the provisions of the latest edition or revision of the relevant standards and codes shall apply, unless otherwise expressly stated in the Contract. Where such standards and codes are national or relate to a particular country or region, other authoritative standards that ensure substantial equivalence to the standards and codes specified will be acceptable.

Reference to brand name and catalogue number should be avoided as far as possible; where unavoidable they should always be followed by the words "or at least equivalent." References to brand names cannot be used when the funding source is the GOP.

Where appropriate, drawings, including site plans as required, may be furnished by the Procuring Entity with the Bidding Documents. Similarly, the Supplier may be requested to provide drawings or samples either with its Bid or for prior review by the Procuring Entity during contract execution.

Bidders are also required, as part of the technical specifications, to complete their statement

of compliance demonstrating how the items comply with the specification.

Technical Specifications

		Specifications
Item	Specification	Statement of Compliance
		[Bidders must state here either "Comply" or "Not Comply" against each of the individual parameters of each Specification stating the corresponding performance parameter of the equipment offered. Statements of "Comply" or "Not Comply" must be supported by evidence in a Bidders Bid and cross-referenced to that evidence. Evidence shall be in the form of manufacturer's un-amended sales literature, unconditional statements of specification and compliance issued by the manufacturer, samples, independent test data etc., as appropriate. A statement that is not supported by evidence or is subsequently found to be contradicted by the evidence presented will render the Bid under evaluation liable for rejection. A statement either in the Bidder's statement of compliance or the supporting evidence that is found to be false either during Bid evaluation, post-qualification or the execution of the Contract may be regarded as fraudulent and render the Bidder or supplier liable for prosecution subject to the applicable laws and issuances.]
1.)	Three (3) unit of ANALYTICAL BALANCE Specifications: Model: BP2003P Capacity: 200g Readability: 1mg Scale Size: 80mm Stable Time: 1s Read Ability: 2mg Liner: 3mg N.W.: 6.8kg External Size: 350*215*340mm Package Size: 480*375*515mm G.W.: 8.5kg Work Space Height: 240mm Calibration: External Cal.	

One (1) unit of BIOSAFETY CABINET

Specifications:

External Size: (WxDxH): 700*650*1230mm (without base stand)

Internal Size (WxDxH): 600*500*540mm

Tetsted Opening: Safety Height

200mm(8")

Max Opening: 370mm(15") Inflow Velocity: 0.53/1.025m/s

Down Flow Velocity:

0.33/0.025m/s

HEPA Filter: Two, 99.995% efficiency at 0.3pm. Filter life

indicator

Front Window: Motorized. Single Layer toughened glass

5mm. anti UV Noise: 67 dB

UV Lamp: 15W*1 UV timer, UV life indicator, emission of 253.7 nanometers for most efficient

decontamination LED Lamp: 8W*2 Illumination: 1000Lux Consumption: 700W

Socket: Two, total load of two

sockets: 500W

Display: LCD Display

Control System: Microprocessor Airflow System: 70% air recirculation, 30% air exhaust Visual and Audio Alarm: Filter replacement, window over height, abnormal air flow velocity; High filter pressure

alarm

Materials: work zone - 304 stainless steel, main body - coldrolled steel with anti-bacteria

powder coating

Work Surface Height: 750mm with optional base stand

Power Supply: AC220V/60HZ Standard Accessory: LED Lamp*2, UV Lamp*1, Remote Control, Waterproof sockets*2,

base stand

Optional Accessory: SS Water

tap*1, SS Gas tap*1

Packing Size (without base

stand): Carton: 730*787*1450mm

	Wood: 860*780*1420mm Gross Weight (without base stand): Carton: 120kg wood: 140kg Packing Size (with base stand): Carton: 730*787*1450mm Wood: 860*780*1420mm Gross Weight (with base stand): Carton: 120kg wood: 140kg	
3)	One (1) unit of COLORIMETER	
	Key Features	
	-Advance from visual to electronic color measurement with confidence -Interpret result easily with visual color comparison mode and direct digital reading -Obtain quality checks with the on-screen warning system-results displayed in green, yellow and red -Easily set time, date, preferences, and projects through the intuitive touch screen -Save 20,000 individual readings to the internal memory -Internationally recognized industry standards	
	Includes	
	-plastic and glass curvettes -color reference standards -cell divider -screwdriver -USB power supply and cable -four AA batteries -and hard-sided carrying case	
4)	One (1) unit of CENTRIFUGE	
	Specifications:	
	Max Capacity: 6*50ml Max Speed: 4000rpm Max RCF: 2250xg Timing Range: 99min Speed Precision: 2% Noise: 65dB Consumption: 150w Power Supply: AC220V, 50/60Hz External Size (L*W*H)mm:	

	4704070400	
	450*370*280 Net Weight (kg): 18	
	Package Size (L*W*H)mm:	
	470*400*375	
	Gross Weight(kg): 22	
	Rotor: Angle Rotor	
	no. 4M0001	
	Capacity: 6*50ml	
5)	Two (2) unit of SAFETY	
	CHEMICAL STORAGE	
	SHELF/CABINET	
	Specifications:	
	External dimensions (mm):	
	470x1800x900	
	Inner dimensions (mm):	
	440x860x260 (x3 stages);	
	860x440x382 (x2 stages)	
	Main unit material: 20mm thick	
	particle board (surface: ply	
	plywood (antibacterial),cosmetic board) with rails/steel	
	Shelf load tolerance: Fixed	
	shelf/30 kg, rail shelf/20kg	
	mm Tana: 260, 382 pitch	
	Drawer: 430mm (slide rail shelf)	
	Weight: 81kg	
	Accessories: Drug tray: 9 pieces	
	Consolidated metal bracket: bolt	
	x 2 pieces	
	Fixed metal bracket: L metal	
	bracket x 2 pieces	
6)	Three (3) unit of BINOCULAR 5	
	MP DIGITAL MICROSCOPE	
	Specifications:	
	-Binocular model	
	-Integrated 5.0 MP CMOS color	
	USB.2 camera	
	-2592x1944 pixels	
	-7 frames per second (2592x1944 pixels)	
	-27 frames per second (1280x960	
	pixels)	
	-Imagefocus Alpha software	
	-CAMERA: -digital bScope	
	microscopes	
	-5.0 MP 1/2.5 inch CMOS USB-	
	2.0 camera, 24 bits color depth, 7	
	frames-per second (1280x960	
	pixels)	
	-dynamic range is 76 db and	
	signal/noise ratio 41 db	

	supplied with ImageFeaus	
7)	-supplied with ImageFocus Alpha Software -USB-2.0 cable and a micrometer 1mm/100 calibration slide -SOFTWARE: the capture and analysis imagefocus alpha software allows to save images in .jpeg, .tif, .bmp or dicom formats as well as .avi format videos. measurements and annotations can be done on live or captured images. compatible with windows 7, 8 and 10 both 32 and 64 bits configurations. a Mac OS version is also available. Free updates can be downloaded from our website. Two (2) unit of DIGITAL	
//	VERNIER CALIPER 150mm STAINLESS STEEL	
	Specifications:	
	Type: Digital Igaging Ez Cal Ip54 0-12" Super Large Lcd Display Digital Caliper Igaging Igaging Ez Cal Ip54 0-12" Super Large Lcd Display Digital Caliper	
8)	One (1) unit of LABORATORY WATER DISTILLER DISTILLING APPARATUS	
	Specifications:	
	Voltage: 110-120 volt Water Flow Rate: 1 litre/minute or higher	
	Water Pressure: Minimum Pressure 3 p.s.i Distillate Temperature: 25-35 Degree C	
	Conductivity: 3.0 - 4.0 S per cm Water Still Output: 4 liters/hour or higher PH: 5.0 - 6.5.	
9)	One (1) unit of FUMEHOOD	
	Specifications:	
	External Size (W*D*H): 1000*800*2515mm Instrument Size (W*D*H): 790*600*870mm	

	Work Surface Height: 900mm	
	Max Opening: 750mm	
	Air Velocity: 0.3~0.8m/s	
	System Exhaust Volume:	
	570m3/h	
	Power Supply: 220V/60Hz	
	Switches: Fan & Light	
	Sash: Safety Glass	
	Superstructure: Epoxy powder	
	coated Steel	
	Inner Liner: Acid & Alkali	
	resistant fiber glass	
	Base Cabinet: Safety storage	
	cabinet or normal base cabinet	
	Water outlet & cupsink:	
	Polypropylene or epoxy resin	
	cupsink	
	Work top: Chemical resistant	
	worktop	
	Color coded for gas and water	
	valve	
	Remote control	
	With complete accessories and	
	Installation	
	With On Site Training	
	With On Site Training	
10)	Five (5) unit of HOTPLATE with	
10)	MAGNETIC STIRRER	
	Specifications:	
	-	
	i vvoik maie immension ivv x im	
	Work plate Dimension (W x D):	
	184 x 184mm	
	184 x 184mm (7 inch)	
	184 x 184mm (7 inch) Work Plate Material: White	
	184 x 184mm (7 inch) Work Plate Material: White Glass Ceramic	
	184 x 184mm (7 inch) Work Plate Material: White Glass Ceramic Motor Type: Brushless DC	
	184 x 184mm (7 inch) Work Plate Material: White Glass Ceramic Motor Type: Brushless DC Motor	
	184 x 184mm (7 inch) Work Plate Material: White Glass Ceramic Motor Type: Brushless DC Motor Stirring Position: 1	
	184 x 184mm (7 inch) Work Plate Material: White Glass Ceramic Motor Type: Brushless DC Motor Stirring Position: 1 Max. Stirring Quantity: 20L	
	184 x 184mm (7 inch) Work Plate Material: White Glass Ceramic Motor Type: Brushless DC Motor Stirring Position: 1 Max. Stirring Quantity: 20L Max. Magnetic Bar (Length):	
	184 x 184mm (7 inch) Work Plate Material: White Glass Ceramic Motor Type: Brushless DC Motor Stirring Position: 1 Max. Stirring Quantity: 20L Max. Magnetic Bar (Length): 80mm	
	184 x 184mm (7 inch) Work Plate Material: White Glass Ceramic Motor Type: Brushless DC Motor Stirring Position: 1 Max. Stirring Quantity: 20L Max. Magnetic Bar (Length): 80mm Speed Range: 100~2000rpm,	
	184 x 184mm (7 inch) Work Plate Material: White Glass Ceramic Motor Type: Brushless DC Motor Stirring Position: 1 Max. Stirring Quantity: 20L Max. Magnetic Bar (Length): 80mm Speed Range: 100~2000rpm, Resolution±1rpm	
	184 x 184mm (7 inch) Work Plate Material: White Glass Ceramic Motor Type: Brushless DC Motor Stirring Position: 1 Max. Stirring Quantity: 20L Max. Magnetic Bar (Length): 80mm Speed Range: 100~2000rpm, Resolution±1rpm Speed Display: LCD	
	184 x 184mm (7 inch) Work Plate Material: White Glass Ceramic Motor Type: Brushless DC Motor Stirring Position: 1 Max. Stirring Quantity: 20L Max. Magnetic Bar (Length): 80mm Speed Range: 100~2000rpm, Resolution±1rpm Speed Display: LCD Temp. Display: LCD	
	184 x 184mm (7 inch) Work Plate Material: White Glass Ceramic Motor Type: Brushless DC Motor Stirring Position: 1 Max. Stirring Quantity: 20L Max. Magnetic Bar (Length): 80mm Speed Range: 100~2000rpm, Resolution±1rpm Speed Display: LCD	
	184 x 184mm (7 inch) Work Plate Material: White Glass Ceramic Motor Type: Brushless DC Motor Stirring Position: 1 Max. Stirring Quantity: 20L Max. Magnetic Bar (Length): 80mm Speed Range: 100~2000rpm, Resolution±1rpm Speed Display: LCD Temp. Display: LCD	
	184 x 184mm (7 inch) Work Plate Material: White Glass Ceramic Motor Type: Brushless DC Motor Stirring Position: 1 Max. Stirring Quantity: 20L Max. Magnetic Bar (Length): 80mm Speed Range: 100~2000rpm, Resolution±1rpm Speed Display: LCD Temp. Display: LCD Heating Temp. Range: Room	
	184 x 184mm (7 inch) Work Plate Material: White Glass Ceramic Motor Type: Brushless DC Motor Stirring Position: 1 Max. Stirring Quantity: 20L Max. Magnetic Bar (Length): 80mm Speed Range: 100~2000rpm, Resolution±1rpm Speed Display: LCD Temp. Display: LCD Heating Temp. Range: Room Temp5000C, Increment 10C	
	184 x 184mm (7 inch) Work Plate Material: White Glass Ceramic Motor Type: Brushless DC Motor Stirring Position: 1 Max. Stirring Quantity: 20L Max. Magnetic Bar (Length): 80mm Speed Range: 100~2000rpm, Resolution±1rpm Speed Display: LCD Temp. Display: LCD Heating Temp. Range: Room Temp5000C, Increment 10C Temp. Control Accuracy: ±10C	
	184 x 184mm (7 inch) Work Plate Material: White Glass Ceramic Motor Type: Brushless DC Motor Stirring Position: 1 Max. Stirring Quantity: 20L Max. Magnetic Bar (Length): 80mm Speed Range: 100~2000rpm, Resolution±1rpm Speed Display: LCD Temp. Display: LCD Temp. Display: LCD Heating Temp. Range: Room Temp5000C, Increment 10C Temp. Control Accuracy: ±10C (<1000C) ±1% (>1000C)	
	184 x 184mm (7 inch) Work Plate Material: White Glass Ceramic Motor Type: Brushless DC Motor Stirring Position: 1 Max. Stirring Quantity: 20L Max. Magnetic Bar (Length): 80mm Speed Range: 100~2000rpm, Resolution±1rpm Speed Display: LCD Temp. Display: LCD Heating Temp. Range: Room Temp5000C, Increment 10C Temp. Control Accuracy: ±10C (<1000C) ±1% (>1000C) Max. Heating plate Temp.: up to 5500C	
	184 x 184mm (7 inch) Work Plate Material: White Glass Ceramic Motor Type: Brushless DC Motor Stirring Position: 1 Max. Stirring Quantity: 20L Max. Magnetic Bar (Length): 80mm Speed Range: 100~2000rpm, Resolution±1rpm Speed Display: LCD Temp. Display: LCD Temp. Display: LCD Heating Temp. Range: Room Temp5000C, Increment 10C Temp. Control Accuracy: ±10C (<1000C) ±1% (>1000C) Max. Heating plate Temp.: up to 5500C Overheating Protection: 5800C	
	184 x 184mm (7 inch) Work Plate Material: White Glass Ceramic Motor Type: Brushless DC Motor Stirring Position: 1 Max. Stirring Quantity: 20L Max. Magnetic Bar (Length): 80mm Speed Range: 100~2000rpm, Resolution±1rpm Speed Display: LCD Temp. Display: LCD Heating Temp. Range: Room Temp5000C, Increment 10C Temp. Control Accuracy: ±10C (<1000C) ±1% (>1000C) Max. Heating plate Temp.: up to 5500C Overheating Protection: 5800C Temp. Display Accuracy: ±10C	
	184 x 184mm (7 inch) Work Plate Material: White Glass Ceramic Motor Type: Brushless DC Motor Stirring Position: 1 Max. Stirring Quantity: 20L Max. Magnetic Bar (Length): 80mm Speed Range: 100~2000rpm, Resolution±1rpm Speed Display: LCD Temp. Display: LCD Heating Temp. Range: Room Temp5000C, Increment 10C Temp. Control Accuracy: ±10C (<1000C) ±1% (>1000C) Max. Heating plate Temp.: up to 5500C Overheating Protection: 5800C Temp. Display Accuracy: ±10C External Temp. Sensor: PT1000	
	184 x 184mm (7 inch) Work Plate Material: White Glass Ceramic Motor Type: Brushless DC Motor Stirring Position: 1 Max. Stirring Quantity: 20L Max. Magnetic Bar (Length): 80mm Speed Range: 100~2000rpm, Resolution±1rpm Speed Display: LCD Temp. Display: LCD Temp. Display: LCD Heating Temp. Range: Room Temp5000C, Increment 10C Temp. Control Accuracy: ±10C (<1000C) ±1% (>1000C) Max. Heating plate Temp.: up to 5500C Overheating Protection: 5800C Temp. Display Accuracy: ±10C External Temp. Sensor: PT1000 (Accuracy ±0.20C)	
	184 x 184mm (7 inch) Work Plate Material: White Glass Ceramic Motor Type: Brushless DC Motor Stirring Position: 1 Max. Stirring Quantity: 20L Max. Magnetic Bar (Length): 80mm Speed Range: 100~2000rpm, Resolution±1rpm Speed Display: LCD Temp. Display: LCD Heating Temp. Range: Room Temp5000C, Increment 10C Temp. Control Accuracy: ±10C (<1000C) ±1% (>1000C) Max. Heating plate Temp.: up to 5500C Overheating Protection: 5800C Temp. Display Accuracy: ±10C External Temp. Sensor: PT1000	

	<u></u>	
12)	Three (3) unit of BENCH TOP pH METER Specifications: PH Range: 0.00~14.00ph PH Accuracy: 0.05ph Resolution: 0.01ph Calibration Points: 2 points Calibration solutions: (ph4.01/7.00/10.01) mV Range: -1999~1999mV mV Accuracy: 10mV Resolution: 1mV Temperature Compensation: 0~100 celcius, manual Connector: BNC, 3.5mm jack socket Display: LCD Power Requirements: DC9V/400mA power adapter Dimensions(mm): at least 210*205*65 Two (2) unit of SOIL	
12)	Two (2) unit of SOIL MOISTURE TESTER/METER Specifications: Sensor Type: PIN Content Analyzer/Range: 0~80% Digital Display: LCD Restore: 99 groups of measurements Accuracy: ± (0.5% n+1) or higher Resolution: 0.1 Condition Temp.: 0~500C Humidity: <90% RH Power Supply: 4 x 1.5 V Statistical Available: LastValue/MeanValue/Max Value, Min Value/Number of Readings	
13)	One (1) unit of ADJUSTABLE VOLUME PIPETTOR (10-100µl) Specifications: Chemical resistant PTFE O-rings and seals that can handle solvents PDF nozzle and PP shaft Fully autoclavable UV resistant for flexible sterilization One touch calibration Wetted materials are made up of at least stainless steel (SS) and polypropylene (PP) plunger assembly Volume of 10-100µL	

	Increments of 0.1µL	
	Accuracy of $\pm 2.0\%$ to $\pm 0.8\%$	
	Tip ejector is present	
	Comes with pipette tips	
	(1000pcs/pack)	
1.4)	E (A) 't -f COH	
	Four (4) unit of SOIL	
	PARAMETER SENSOR SET	
	Compose of the ff. sensors:	
	Soil Nitrogen Concentration	
	Sensor	
	Soil Phosphorus Concentration	
	Sensor Soil Potassium Concentration	
	Sensor	
	Range: 1-999mg/kg	
	±2% F.S	
15)	One (1) unit of	
/	SPECTROPHOTOMETER	
	Specifications:	
	Optical System: Single beam,	
	grating 1200lines/mm	
	Wavelength range: 200-1020mm	
	Spectral bandwith: 4nm	
	Wavelength accuracy: 1.8nm	
	Wavelength repeatability: 0.5nm	
	Photometric Accuracy:	
	0.002A(0-0.5Abs), 0.004A (0.5-	
	1.0Abs), 0.5%T (0-100%T)	
	Photometric repeatability:	
	0.001Abs(0-0.5Abs), 0.002Abs	
	(0.5-1Abs), 0.2%T (0-100%T)	
	Stray light: 0.2%T @ 360nm;	
	220nm (UV)	
	Stability: 0.002A/h@500nm	
	Noise: 0.001A	
	Display: 128*64 Dots LCD	
	Photometric Mode: T, A, C, E	
	Photometric range: 0-200%T,-	
	0.301~3.0A	
	Detector: Silicon Photodiode	
	Light Source: Deuterium lamp,	
	tungsten lampInput: Membrane	
	keypad	
	Output: Parallel Print, USB 1.0	
	Standard Accessories: 1cm glass	
	cuvette *4 units 1cm quartz	
	cuvette *2 1cm quadruple cuvette	
	holder *1	
	Optional Accessories: General	
	application software, 1cm	
	standard single lot cuvette holder,	
	long optical path cuvette holder,	
	cuvette, micro cuvette, test tube	
	type absorber rack, solid sample	
	holder, deuterium lamp, tungsten	

	lamp, quadruple cuvette holder, printer, four slot water bath type constant temperature absorption pool, X-Y adjustable micro absorption pool, single bath type constant temperature absorption pool . Power Supply: AC110V/220 10%, 60/50Hz - With On Site Training	
16)	E (4) 4 - FI ADOD ATODY	
16)	Four (4) unit of LABORATORY STAINLESS CART Specifications: Material: Solid Stainless Steel Capacity: At least 700lbs Dimension: 24"W x 26"L x 36"H Layers:3 With Handle	
17)	Two (2) unit of UV STERILIZATION CABINET Specifications: Type: with Ozone UV Ray Wavelength: 253.7/184.9nm Sterilization Way: 2 sides of UV ray+1 side of Ozone Capacity: 200L Power: 120W UV Lamp Materials: Quartz glass Shelves: Standard 2pc. can be optional Internal Size: at least 518x523x778mm External Size: at least 750x663x1200mm	
18)	Two (2) unit of DIGITAL WEIGHING SCALE Specifications: Weighing capacity: 15kg or higher Scale type: Bench Resolution: 87.5 Plug Type: type C-European Plug Weigh pan Length: 285mm Weigh pan Width: 255mm Weigh pan Height: 90mm Net Weight: 3.75kg or higher Min. Operating Temp.: +10 degree celcius Min. Operating Temp.: +35	

	degree celcius.	
19)	Four (4) unit of PORTABLE TEMPERATURE AND HUMIDITY DATA LOGGER Specifications: Temp. Range: -40 degree celcius~85 degree celcius Humidity Range: 0~100% RH Temperature Accuracy: 0.5 Humidity Accuracy: 3% RH Temperature Resolution: 0.10C Humidity Resolution: 3% RH Recording capacity: 16000 points(MAX).	

Section VIII. Checklist of Technical and Financial Documents

Notes on the Checklist of Technical and Financial Documents

The prescribed documents in the checklist are mandatory to be submitted in the Bid, but shall be subject to the following:

- a. GPPB Resolution No. 09-2020 on the efficient procurement measures during a State of Calamity or other similar issuances that shall allow the use of alternate documents in lieu of the mandated requirements; or
- b. Any subsequent GPPB issuances adjusting the documentary requirements after the effectivity of the adoption of the PBDs.

The BAC shall be checking the submitted documents of each Bidder against this checklist to ascertain if they are all present, using a non-discretionary "pass/fail" criterion pursuant to Section 30 of the 2016 revised IRR of RA No. 9184.

Checklist of Technical and Financial Documents

I. TECHNICAL COMPONENT ENVELOPE

Class "A" Documents Legal Documents \sqcap (a) Valid PhilGEPS Registration Certificate (Platinum Membership) (all pages) in accordance with Section 8.5.2 of the IRR: **Technical Documents** Statement of the prospective bidder of all its ongoing government and □ (b) private contracts, including contracts awarded but not yet started, if any, whether similar or not similar in nature and complexity to the contract to be □ (c) Statement of the bidder's Single Largest Completed Contract (SLCC) similar to the contract to be bid, except under conditions provided for in Sections 23.4.1.3 and 23.4.2.4 of the 2016 revised IRR of RA No. 9184, within the relevant period as provided in the Bidding Documents; and Original copy of Bid Security. If in the form of a Surety Bond, submit also a \square (d) certification issued by the Insurance Commission or Original copy of Notarized Bid Securing Declaration; and Conformity with the Technical Specifications, which may include □ (e) production/delivery schedule, manpower requirements, and/or aftersales/parts, if applicable; and Original duly signed Omnibus Sworn Statement (OSS) and if applicable, \sqcap (f) Original Notarized Secretary's Certificate in case of a corporation, partnership, or cooperative; or Original Special Power of Attorney of all members of the joint venture giving full power and authority to its officer to sign the OSS and do acts to represent the Bidder. Financial Documents The prospective bidder's computation of Net Financial Contracting \sqcap (g) Capacity (NFCC) or A committed Line of Credit from a Universal or Commercial Bank in lieu of its NFCC computation. Class "B" Documents If applicable, a duly signed joint venture agreement (JVA) in case the joint \Box (h) venture is already in existence or duly notarized statements from all the potential joint venture partners stating that they will enter into and abide by the provisions of the JVA in the instance that the bid is successful. II. FINANCIAL COMPONENT ENVELOPE Original of duly signed and accomplished Financial Bid Form; and ☐ (i) Original of duly signed and accomplished Price Schedule(s). \square (j)

Other documentary requirements under RA No. 9184 (as applicable)

- [For foreign bidders claiming by reason of their country's extension of reciprocal rights to Filipinos] Certification from the relevant government office of their country stating that Filipinos are allowed to participate in government procurement activities for the same item or product.
- □ (1) Certification from the DTI if the Bidder claims preference as a Domestic Bidder or Domestic Entity.

